

Empresa

EMC Brasil

TERMO DE ACEITE TÉCNICO

Plataforma

VSAT

Link kbps

256k/128k


Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Guilherme Henrique

Cliente: VIVO

VSAT-ID

VIVO-PER-23097787-CE



dvb tx show

Satellite (DVB) TX Configuration

Auto start : Enabled IDU Output Power : -15 dBm IDU Max Output Power: 0.0 dBm ODU Output Power : max

EIRP : max

Default CW Frequency: 0.000000 GHz

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

State : On (DVB-RCS2) IDU Output Power : -16.7 dBm ODU Output Power : 35.4 dBm

EIRP : 48.7 dBW Es/No : 10.0 dB

Header Compression: Disabled

Timing correction : -51 us (253944 us)

Frequency correction: -90 Hz

dvb rx show

Satellite (DVB) RX Configuration

Auto start : Enabled

Max Traffic MODCOD : 23 16APSK-9/10

RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName Name Enable

* 0 0 15.000000 12.059000 DVB-S2 102 0 0.0 E Yes 1 1 9.320000 12.055825 DVB-S2 4 0 0.0 E No

Satellite (DVB) Receiver Status

Rx State : On

DVB State : Forward link up Network : 1326, T14R Beam Frequency : 12.059042 GHz Symbol Rate : 15.000189 Msps

S2 ModCod

- receiving : 12 8PSK-3/5 - current max : 22 16APSK-8/9

Pilot : On

Frame length : Short DVB S2 Mode : ACM

DVB S2 Stream type: MPEG-TS

Roll off : 0.20 SNR : 15.0 dB Input Power : -26 dBm

