



TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Leonardo Martins

Cliente: VIVO

Empresa
EMC Brasil

VSAT-ID
VIVO-PER-22053387-CE

Link kbps
256k/128k

Plataforma
VSAT

dvb tx show

Satellite (DVB) TX Configuration

Auto start : Enabled
IDU Output Power : -15 dBm
IDU Max Output Power: 0.0 dBm
Default CW Frequency: 0.000000 GHz
ATM mode : VC-Mux
Header Compression : None

Satellite (DVB) Transmitter Status

State : On (DVB-RCS2)
IDU Output Power : -15.1 dBm
Es/No : 12.0 dB
Header Compression : Disabled
Timing correction : -21 us (252735 us)
Frequency correction: 150 Hz
dvb rx show

Satellite (DVB) RX Configuration

Auto start : Enabled
Max Traffic MODCOD : 23 16APSK-9/10
RX watchdog : 15 minute

Idx	Pri	SymbRate[Msp/s]	Freq[GHz]	Mode	PopId	SatId	Pos	SatName	Name
Enable									
* 0	0	15.000000	12.059000	DVB-S2	102	0	0.0 E		
Yes									
1	1	9.320000	12.055825	DVB-S2	4	0	0.0 E		
Yes									

Satellite (DVB) Receiver Status

Rx State : On
DVB State : Forward link up
Network : 1326, T14R Beam
Frequency : 12.059095 GHz
Symbol Rate : 14.999902 Msp/s
S2 ModCod
- receiving : 20 16APSK-4/5
- current max : 20 16APSK-4/5
Pilot : On
Frame length : Short
DVB S2 Mode : ACM
DVB S2 Stream type : MPEG-TS
Roll off : 0.20

```
SNR                : 13.5 dB
Input Power        : -33 dBm
#
# ping 8.8.8.8
64 bytes from 8.8.8.8: time=830 ms
64 bytes from 8.8.8.8: time=690 ms
64 bytes from 8.8.8.8: time=730 ms
64 bytes from 8.8.8.8: time=690 ms
64 bytes from 8.8.8.8: time=740 ms

--- ping statistics ---
5 packets transmitted, 5 received, 0.00 percent packet loss
rtt min/avg/max = 690/730/830 ms
#
```