

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Rogerio Momi Frias


Cliente: VIVO

Empresa
EMC Brasil

VSAT-ID
VIVO-PER-31024074-MG

Link kbps
256/128

Plataforma
VSAT



Satellite (DVB) RX Configuration

Auto start : Enabled
Max MODCOD : 23 16APSK-9/10 (SNR threshold: 23.5 dB)
RX watchdog : 15 minute
Idx Pri SymbRate[Mbps] Freq[GHz] Mode PopId Enable
* 0 0 9.320000 12.055825 DVB-S2 4 Yes
1 1 0.000000 0.000000 DVB-S2 2 Yes
Satellite (DVB) Receiver Status

Rx State : On
DVB State : Forward link up
Network : 1326, GlobalIP@Telstar-14R
Frequency : 12.055824 GHz
Symbol Rate : 9.319898 Msps
S2 ModCod
- receiving : 1 QPSK-1/4
- current max : 23 16APSK-9/10
Pilot : On
Frame length : Short
DVB S2 Mode : ACM
Roll off : 0.25
SNR : 14.1 dB
Input Power : -26 dBm

Satellite (DVB) TX Configuration

Auto start : Enabled
IDU Output Power : -30 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : 34.7 dBm
EIRP : 48.0 dBW
Default CW Frequency: 0.000000 GHz
ATM mode : VC-Mux
Header Compression : None
Satellite (DVB) Transmitter Status

State : On (TDMA)
IDU Output Power : -16.2 dBm
ODU Output Power : 34.5 dBm
EIRP : 47.8 dBW
Eb/No : 14.5 dB
Header Compression : Disabled
Timing correction : -250 us (261625 us)
Frequency correction: -190 Hz

ping 8.8.8.8
64 bytes from 8.8.8.8: time=2170 ms
64 bytes from 8.8.8.8: time=890 ms
64 bytes from 8.8.8.8: time=940 ms
64 bytes from 8.8.8.8: time=730 ms
64 bytes from 8.8.8.8: time=540 ms
--- 8.8.8.8 ping statistics ---
5 packets transmitted, 5 received, 0.00 percent packet loss
rtt min/avg/max = 540/1050/2170 ms