



# TERMO DE ACEITE TÉCNICO

Solicitante: VIVO

NOC/Operador: Vitor Hugo

Cliente: VIVO

Empresa EMC  
Brasil

VSAT-ID  
VIVO-PER-23044268-CE

Link kbps  
1024k/256k

Plataforma VSAT



```
ca. Administrador: Prompt de Comando
Microsoft Windows [versão 6.1.7601]
Copyright (c) 2009 Microsoft Corporation. Todos os direitos reservados.

C:\Users\Asus>ping 8.8.8.8 -t

Disparando 8.8.8.8 com 32 bytes de dados:
Resposta de 8.8.8.8: bytes=32 tempo=567ms TTL=118
Resposta de 8.8.8.8: bytes=32 tempo=654ms TTL=118
Resposta de 8.8.8.8: bytes=32 tempo=721ms TTL=118
Resposta de 8.8.8.8: bytes=32 tempo=789ms TTL=118
Resposta de 8.8.8.8: bytes=32 tempo=885ms TTL=118
Resposta de 8.8.8.8: bytes=32 tempo=964ms TTL=118
Resposta de 8.8.8.8: bytes=32 tempo=1025ms TTL=118
Resposta de 8.8.8.8: bytes=32 tempo=720ms TTL=118
Resposta de 8.8.8.8: bytes=32 tempo=1153ms TTL=118
Resposta de 8.8.8.8: bytes=32 tempo=1441ms TTL=118
Resposta de 8.8.8.8: bytes=32 tempo=969ms TTL=118
Resposta de 8.8.8.8: bytes=32 tempo=1878ms TTL=118
Resposta de 8.8.8.8: bytes=32 tempo=719ms TTL=118
Resposta de 8.8.8.8: bytes=32 tempo=795ms TTL=118
Resposta de 8.8.8.8: bytes=32 tempo=892ms TTL=118
Resposta de 8.8.8.8: bytes=32 tempo=599ms TTL=118

Estatísticas do Ping para 8.8.8.8:
    Pacotes: Enviados = 16, Recebidos = 16, Perdidos = 0 (0% de
    perda).
Aproximar um número redondo de vezes em milissegundos:
    Mínimo = 567ms, Máximo = 1878ms, Média = 923ms
Control-C
^C
C:\Users\Asus>arp -a

Interface: 10.29.76.75 --- 0xc
Endereço IP      Endereço físico      Tipo
10.29.76.73      00-20-0e-10-88-5f    dinâmico
10.29.76.79      ff-ff-ff-ff-ff-ff    estático
224.0.0.2        01-00-5e-00-00-02    estático
224.0.0.22       01-00-5e-00-00-16    estático
224.0.0.251      01-00-5e-00-00-fb    estático
224.0.0.252      01-00-5e-00-00-fc    estático
239.255.255.250  01-00-5e-7f-ff-fa    estático
255.255.255.255  ff-ff-ff-ff-ff-ff    estático

C:\Users\Asus>UIU0-PER-23044268-CE-APUIARES-CE
```

```
Telnet 10.29.76.73
Login: Password: Access Denied
Login: Password:
SatLink 2000
- Main board IS 128026, Revision R6.2
- SV 128010 17.0.4 Build 114
0
Satellite (DDE) TX Configuration
Auto start : Disabled
DDE Status : Disabled
DDE Output Power : -10 dBm
DDE Max Output Power: 0.0 dBm
Default Qr Frequency: 0.000000 GHz
QTN mode : SC-Mux
Header Compression : None

Satellite (DDE) Transmitter Status
State : On (DDE-RC32)
DDE Output Power : -10.4 dBm
EIRP : 13.0 dB
Header Compression : Disabled
Timing correction : -41 ns (248517 ns)
Frequency correction: 790 Hz
0
Satellite (DDE) RX Configuration
Auto start : Enabled
Max Signalling MODCOD : 23 16QPSK-9/10
Max Traffic MODCOD : 28 32QPSK-9/10
RS watchdog : 15 minutes
Idx Pri SynchState(Maps) Freq(GHz) Mode PopId SatId Pos SatName
Name Enable
* 0 0 38.000000 11.592000 DVB-S2 100 0 0.0 E
Yes
Satellite (DDE) Receiver Status
Rx State : On
DVB State : Forward link up
Network : 1326, 1140 Beam
Frequency : 11.592074 GHz
Symbol Rate : 38.000528 Msps
S2 ModCod :
- receiving : 13 8PSK-2/3
- current max : 21 16QPSK-5/6
Pilot : On
Frame length : Short
DVB S2 Mode : ACM
DVB S2 Stream type : ATSC-1E
Roll off : 0.20
SNR : 13.6 dB
Input Power : -35 dBm
0
```

SatLink-VSAT

Não seguro | 10.29.76.73/vm/dap/index\_p...

Apps | Bookmarks | Chat com nitor.com | Mensagem de Aniv...

SatLink

Status

Satellite

Statistics

Device

DWCP

Eventlog

Configuration

Satellite

IP

Static NAT

Lineup

Device

Tools

Help

Introduction

Status

Configuration

Device Status

Model	SatLink 2000
Software Version	17.0.4.114
LAN MAC Address	00.20.0e.10.88.5f
DVB MAC Address	00.20.0e.10.88.5f
System Up Time	0 days, 00:02:35
CPU Load	28%
System Name	VIVO-PER-23044268-CE
System Contact	
System Location	APUIARES-CE

You are logged in as install (2) on VIVO-PER-23044268-CE

© Copyright 2016-2018 Nitor Global Technologies A/S. All Rights Reserved.

```
ca. Administrador: Prompt de Comando
Microsoft Windows [versão 6.1.7601]
Copyright (c) 2009 Microsoft Corporation. Todos os direitos reservados.

C:\Users\Asus>tracert 8.8.8.8

Rastreando a rota para google-public-dns-a.google.com [8.8.8.8]
com no máximo 30 saltos:

 1  <1 ms    <1 ms    <1 ms    10.29.76.73
 2  *        *        *        Esgotado o tempo limite do pedido.
 3  1149 ms  1046 ms  1104 ms  172.30.3.102
 4  845 ms  968 ms  1074 ms  92.39.116.18
 5  994 ms  955 ms  1208 ms  static-1.112.39.92.in-addr.arpa [92.39.112.1]
 6  1759 ms  1794 ms  1074 ms  s200-189-162-154.ipb.diveo.net.br [200.189.162.1
54]
 7  1129 ms  1113 ms  1056 ms  200-147-28-129.static.uol.com.br [200.147.28.129
]
 8  1009 ms  1086 ms  1055 ms  as15169.saopaulo.sp.ix.br [187.16.216.55]
 9  1155 ms  1070 ms  1080 ms  108.170.245.161
10  1101 ms  1105 ms  1080 ms  216.239.56.45
11  1056 ms  1104 ms  1090 ms  google-public-dns-a.google.com [8.8.8.8]

Rastreamento concluído.

C:\Users\Asus>arp -a

Interface: 10.29.76.75 --- 0xc
Endereço IP      Endereço físico      Tipo
10.29.76.73      00-20-0e-10-88-5f    dinâmico
10.29.76.79      ff-ff-ff-ff-ff-ff    estático
224.0.0.2        01-00-5e-00-00-02    estático
224.0.0.22       01-00-5e-00-00-16    estático
224.0.0.251      01-00-5e-00-00-fb    estático
224.0.0.252      01-00-5e-00-00-fc    estático
239.255.255.250  01-00-5e-7f-ff-fa    estático
255.255.255.255  ff-ff-ff-ff-ff-ff    estático

C:\Users\Asus>UIUO-PER-23044268-CE--APUIARES-CE
```