



TERMO DE ACEITE TÉCNICO

Solicitante: GEE

NOC/Operador: Rogério Frias

Cliente: Bentley Walker

Empresa
Global Eagle Entertainment

VSAT-ID
EBW-20322

Link kbps
1024k/512k

Plataforma
VSAT

device show

System Information:

Name : EBW-20322
Location : Marã - AM
Contact :
System Up time : 0 days, 00:19:55
CPU Load : 15%
System time(UTC) : 19 June 2017 13:47:36
Broadcast Message : not set

HW:

Model : SatLink 2000
HW ID : 120033
Main board ID : 120026 R6.2

MAC addresses:

Ethernet (LAN) : 00:20:0e:10:83:9e
Satellite (DVB) : 00:20:0e:10:83:9e

dvb rx show

Satellite (DVB) RX Configuration

Auto start : Enabled
Max Traffic MODCOD : 23 16APSK-9/10
RX watchdog : 15 minute

Idx	Pri	SymbRate[Mbps]	Freq[GHz]	Mode	PopId	SatId	Pos	SatName
Name		Enable						
* 0	0	15.000000	12.059000	DVB-S2 4	0	0.0	E	
Yes								
1	1	9.320000	12.055825	DVB-S2 4	0	0.0	E	
Yes								

Satellite (DVB) Receiver Status

Rx State : On
DVB State : Forward link up
Network : 1326, T14R Beam
Frequency : 12.058720 GHz
Symbol Rate : 14.999930 Msps
S2 ModCod
- receiving : 21 16APSK-5/6
- current max : 18 16APSK-2/3
Pilot : On
Frame length : Short
DVB S2 Mode : ACM
DVB S2 Stream type : MPEG-TS
Roll off : 0.20
SNR : 13.1 dB
Input Power : -32 dBm
dvb tx show

Satellite (DVB) TX Configuration

Auto start : Enabled
IDU Output Power : -15 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : 33.7 dBm
EIRP : 47.0 dBW
Default CW Frequency: 14.125850 GHz
ATM mode : VC-Mux
Header Compression : None

Satellite (DVB) Transmitter Status

State : On (DVB-RCS)
IDU Output Power : -13.3 dBm
ODU Output Power : 33.6 dBm
EIRP : 46.9 dBW
Es/No : 13.0 dB
Header Compression : Disabled
Timing correction : -80 us (249795 us)
Frequency correction: -60 Hz
odu show

Antenna

Type ASC/Andrew/Channel Master Type 123 - 1.2m
Antenna controller None
Tx Gain at 14.25 GHz 43.3dB

Transmitter (BUC)

Type SatLink 4033 (14.0-14.5 GHz)
ODU Serial No. 104804040203080509580000
ODU HW Version 4.2
ODU SW Version 1.3
Local oscillator 13.050000 GHz
DC supply 24V On
Temperature 45 Deg C

Receiver (LNB)

Type SatLink 403x (10.70-12.75 GHz)
Local oscillator - LO1 9.750000 GHz
Local oscillator - LO2 10.600000 GHz
Oscillator switching frequency 1-2 11.700000 GHz
LO Switching mode 22kHz
13/18V DC supply 13V

dvb cr show

Capacity parameters per channel:

Channel CRA[kbps] Allocated[kbps]
0 0 7

Requested capacity per QoS class:

Channel CRClass MaxRBDC[kbps] MaxVBDC[kB] RateReq[kbps] VolReq[octs] Description
0 0 612 61 0 0 Best Effort
0 1 0 0 0 0 VoiP
0 2 0 0 0 0 ViC
0 3 32 3 0 0 Critical Data

RBDC timeout 5 VBDC timeout 20

VBDC computation interval 200 ms (configured 0)
ip mfc show
MfC Classification table
Module: PEP (1)
SubIdx Idx Grp Classification Parm s HitCount
1 10 1 Dst port = 1..65535 153
^C