

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Rogério Momi Frias


Cliente: VIVO

Empresa
EMC Brasil

VSAT-ID
VIVO-PER-23126019-CE

Link kbps
256/128

Plataforma
VSAT



Satellite (DVB) RX Configuration

Auto start : Enabled
Max Traffic MODCOD : 23 16APSK-9/10
RX watchdog : 15 minute

Idx	Pri	SymbRate[Mbps]	Freq[GHz]	Mode	PopId	SatId	Pos	SatName	Name	Enable
* 0	0	9.320000	12.055825	DVB-S2 4	0	0.0	E		Yes	

Satellite (DVB) Receiver Status

Rx State : On
DVB State : Forward link up
Network : 1326, GlobalIP@Telstar-14R
Frequency : 12.055957 GHz
Symbol Rate : 9.320031 Msps
S2 ModCod
- receiving : 14 8PSK-3/4
- current max : 16 8PSK-8/9
Pilot : On
Frame length : Short
DVB S2 Mode : ACM
DVB S2 Stream type : MPEG-TS
Roll off : 0.20
SNR : 13.3 dB
Input Power : -29 dBm

Satellite (DVB) TX Configuration

Auto start : Enabled
IDU Output Power : -24 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : 34.6 dBm
EIRP : 45.5 dBW
Default CW Frequency: 14.125750 GHz
ATM mode : VC-Mux
Header Compression : None

Satellite (DVB) Transmitter Status

State : On (DVB-RCS)
IDU Output Power : -25.9 dBm
ODU Output Power : 34.5 dBm
EIRP : 45.4 dBW
Es/No : 11.5 dB
Header Compression : Disabled
Timing correction : -95 us (261217 us)
Frequency correction: -30 Hz

ping 8.8.8.8

64 bytes from 8.8.8.8: time=550 ms
64 bytes from 8.8.8.8: time=620 ms
64 bytes from 8.8.8.8: time=1260 ms
64 bytes from 8.8.8.8: time=620 ms
64 bytes from 8.8.8.8: time=700 ms

--- ping statistics ---

5 packets transmitted, 5 received, 0.00 percent packet loss
rtt min/avg/max = 550/750/1260 ms