


TERMO DE ACEITE TÉCNICO

Solicitante: PRODEMGE / SEE

NOC/Operadora: Wallace Teixeira Operadora/Cliente: Sergio Almeida

GRE/Prodemge: João Antinossi Responsável/cliente: Narciso Afonso

> Plataforma Consórcio **VSAT-ID** Porta kbps EMC/Vodanet **SEE-COUS-23003** 2MBPS **VSAT**



PRTG Traffic Grapher V6.2.0.907 - 25/11/2017 22:56:43

dvb rx show

Satellite (DVB) RX Configuration

Auto start : Enabled
Max Traffic MODCOD : 23 16APSK-9/10
RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName Name

Enable

* 0 0 4.883300 12.176420 DVB-S2 104 0 0.0 E

Yes

1 1 16.667000 11.962753 DVB-S2 2 0 0.0 E

Yes

Satellite (DVB) Receiver Status ______

Rx State : On

Rx State : On
DVB State : Forward link up
Network : 65281, Prodemge@Vodanet
Frequency : 12.176600 GHz
Symbol Rate : 4.882982 Msps

S2 ModCod

- receiving : 4 QPSK-1/2 - current max : 21 16APSK-5/6

Pilot : On Frame length : Short DVB S2 Mode : ACM

```
DVB S2 Stream type : MPEG-TS
Roll off : 0.20
                    : 16.6 dB
SNR
Input Power
                    : -34 dBm
# dvb tx show
Satellite (DVB) TX Configuration
_____
                   : Enabled
Auto start
Auto start : Enabled IDU Output Power : -20 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : 33.2 dBm
EIRP
                    : 46.5 dBW
Default CW Frequency: 0.000000 GHz
ATM mode
                    : VC-Mux
Header Compression : UDP/IP
Satellite (DVB) Transmitter Status
_____
State : On (DVB-RCS2)
IDU Output Power : -6.5 dBm
ODU Output Power : 33.4 dBm
EIRP
EIRP
                    : 46.7 dBW
Es/No
                    : 14.0 dB
{\tt Header\ Compression} : Disabled - HC for RCS2 not supported by HUB
Timing correction : -300 us (281460 us)
Frequency correction: -90 Hz
# device show
System Information:
   Name
                        : SEE-COUS-23003
    Location
                        : Coração de Jesus - MG
    Contact
                        :
    System Up time : 0 days, 07:00:54
CPU Load : 6%
System time(UTC) : 26 November 2017 05:03:07
    Broadcast Message : not set
HW:
    Model
                        : SatLink 2000
    HW ID
                        : 120033
    Main board ID
                       : 120026 R6.2
MAC addresses:
   Ethernet (LAN) : 00:20:0e:10:5c:da Satellite (DVB) : 00:20:0e:10:5c:da
# arp show
   NetAddr State MacAddr
                                             Ιf
[20:15, 25/11/2017] +55 11 96472-6414: Pinging 10.215.211.1 with 32 bytes of data:
Reply from 10.215.211.1: bytes=32 time=538ms TTL=56
Reply from 10.215.211.1: bytes=32 time=575ms TTL=56
Reply from 10.215.211.1: bytes=32 time=582ms TTL=56
Reply from 10.215.211.1: bytes=32 time=555ms TTL=56
Reply from 10.215.211.1: bytes=32 time=667ms TTL=56
Reply from 10.215.211.1: bytes=32 time=755ms TTL=56
Reply from 10.215.211.1: bytes=32 time=574ms TTL=56
Reply from 10.215.211.1: bytes=32 time=554ms TTL=56
Reply from 10.215.211.1: bytes=32 time=557ms TTL=56
Reply from 10.215.211.1: bytes=32 time=579ms TTL=56
Ping statistics for 10.215.211.1:
```

Packets: Sent = 10, Received = 10, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
Minimum = 538ms, Maximum = 755ms, Average = 593ms
TIETIEMAM COOME, IIAIIEMAM , COME, IIVOEAGO COOME
Lista de sites acessados:
<u>www.globo.com</u> – ok
<u>www.yahoo.com</u> – ok
<u>www.hotmail.com</u> – ok
www.google.com – ok
www.educacao.mg.gov.br – ok
www.prodemge.gov.br – ok
The state of the s
D / 1 1 / / 1 ~
Responsável pelo teste de navegação:
Nome: Narciso Afonso
Função: asb
Identidade: Masp: 9807629