


TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Bruno Carvalho de Sá Cliente: VIVO

EmpresaVSAT-IDLink kbpsPlataformaEMC BrasilVIVO-PER-31149179-MG256/128VSAT



Satellite (DVB) TX Configuration

Auto start : Enabled
IDU Output Power : -21 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : 33.7 dBm
EIRP : 47.0 dBW
Default CW Frequency: 0.0000000 GHz

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

State : On (TDMA)

IDU Output Power : -21.8 dBm

ODU Output Power : 33.3 dBm

EIRP : 46.6 dBW

Es/No : 14.5 dB

Header Compression : Disabled

Timing correction : -201 us (261744 us)

Frequency correction: 20 Hz

Satellite (DVB) RX Configuration

Auto start : Enabled

Max MODCOD : 23 16APSK-9/10 (SNR threshold: 23.5 dB)

```
: 15 minute
RX watchdog
Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId Enable
* 0 0 9.320000 12.055825 DVB-S2 102 Yes 1 1 0.000000 0.000000 DVB-S2 2 No
          9.320000
                         12.055825 DVB-S2 4
 4 4
                                                         No
Satellite (DVB) Receiver Status
Rx State : On

DVR State : Forward link up

1326, GlobalIP
Network : 1326, GlobalIP@Telstar-14R
Frequency : 12.055657 GHz
Symbol Rate : 9.319947 Msps
S2 ModCod
   - receiving : 13 8PSK-2/3
- current max : 23 16APSK-9/10
Pilot
                : On
Frame length
                     : Short
DVB S2 Mode
                     : ACM
                    : 0.20
Roll off
SNR : 13.4 dB Input Power : -23 dBm
IP DVB 10.50.1.18 /32
# ping 8.8.8.8
64 bytes from 8.8.8.8: time=1690 ms
64 bytes from 8.8.8.8: time=560 ms
64 bytes from 8.8.8.8: time=570 ms
64 bytes from 8.8.8.8: time=560 ms
64 bytes from 8.8.8.8: time=540 ms
--- 8.8.8.8 ping statistics ---
5 packets transmitted, 5 received, 0.00 percent packet loss
rtt min/avg/max = 540/780/1690 ms
```

