

TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Leonardo Martins Cliente: VIVO

Empresa VSAT-ID Link kbps Plataforma EMC Brasil VIVO-PER-28012526-SE 256k/128k **VSAT**

device show

System Information:

: VIVO-PER-28012526-SE Name Location : RIACHAO DOS DANTAS - SE

Contact

System Up time : 1 day, 03:19:27

CPU Load : 29%
System time(UTC) : 09 February 2018 15:30:56
Broadcast Message : not set

HW:

: SatLink 2000 Model HW ID Main board ID Model : 120033 : 120026 R6.2

MAC addresses:

Ethernet (LAN) : 00:20:0e:10:7c:28 Satellite (DVB) : 00:20:0e:10:7c:28

dvb tx show

Satellite (DVB) TX Configuration

Auto start : Enabled IDU Output Power : -15 dBm Auto start

IDU Max Output Power: 0.0 dBm Default CW Frequency: 0.000000 GHz

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

State : On (DVB-RCS2)
IDU Output Power : -14.8 dBm
Es/No : 10.5 dB Header Compression : Disabled

Timing correction : -124 us (249725 us)

Frequency correction: 40 Hz

dvb rx show

Satellite (DVB) RX Configuration Auto start : Enabled

Max Traffic MODCOD : 23 16APSK-9/10 RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName Name

Enable

30.000000 12.050000 DVB-S2 102 0 0.0 E * 0 0 Yes

0 0.0 E 1 1 25.333333 12.050000 DVB-S2 4

No

Satellite (DVB) Receiver Status _____

Rx State : On DVB State : Forward link up
Network : 1326, T14R Beam
Frequency : 12.050061 GHz
Symbol Rate : 30.000407 Msps S2 ModCod - receiving : 18 16APSK-2/3 - current max : 22 16APSK-8/9 Pilot : On Frame length : Short DVB S2 Mode : ACM DVB S2 Stream type : MPEG-TS Roll off : 0.20 SNR : 14.6 dB : -31 dBm Input Power # dvb cr show Capacity parameters per channel: _____ Channel CRA[kbps] Allocated[kbps] 0 0 Requested capacity per QoS class: _____ Channel CRClass MaxRBDC[kbps] MaxVBDC[kB] RateReq[kbps] VolReq[octs] Description 0 0 200 20 0 0 Best Effort
0 1 0 0 0 0 0 0 VoIP
0 2 0 0 0 0 0 ViC
0 3 32 3 0 0 Critical Date 0 Critical Data RBDC timeout 14 VBDC timeout 20 VBDC computation interval 200 ms (configured 0)