

TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Leonardo Martins

Cliente: VIVO

Empresa
EMC Brasil

VSAT-ID
VIVO-PER-22065717-PI

Link kbps
256k/128k

Plataforma
VSAT



```
Telnet 10.29.37.49
Login: Password:
SatLink 2000
- Main board ID 120026, Revision R6.2
- SV ID 120200, Revision 16.0.1 Build 57
Satellite <DUB> TX Configuration
Auto start : Enabled
IDU Output Power : -15 dBm
IDU Max Output Power: 0.0 dBm
Default CW Frequency: 0.000000 GHz
ATM mode : UC-Mux
Header Compression : None

Satellite <DUB> Transmitter Status
State : On <DUB-BCS2>
IDU Output Power : -15.1 dBm
Ex/No : 14.5 dB
Header Compression : Disabled
Timing correction : -121 us (252951 us)
Frequency correction: -20 Hz
```

```
Telnet 10.29.37.49

Idx  Pri  SynbRate[Mbps] Freq[GHz] Mode  PopId  SatId  Fox  SatName
Name  Enable
* 0 0 15.000000 12.059000 DUB-S2 102 0 0.0 E
1 1 9.320000 12.055025 DUB-S2 4 0 0.0 E

Satellite (DUB) Receiver Status
Rx State : On
DUB State : Forward link up
Network : 1326, T14R Beam
Frequency : 12.059004 GHz
Symbol Rate : 14.999709 Mbps
S2 ModCod
- receiving : 12 8PSK-3/5
- current max : 22 16APSK-0/9
Pilot : On
Frame length : Short
DUB S2 Mode : ACH
DUB S2 Stream type : MPEG-TS
Roll off : 0.20
SNR : 15.0 dB
Input Power : -41 dBm
S
```

```
cmd - Atalho

Resposta de 0.0.0.0: bytes=32 tempo=2550ms TTL=55
Resposta de 0.0.0.0: bytes=32 tempo=714ms TTL=55
Resposta de 0.0.0.0: bytes=32 tempo=792ms TTL=55
Resposta de 0.0.0.0: bytes=32 tempo=870ms TTL=55
Resposta de 0.0.0.0: bytes=32 tempo=595ms TTL=55
Resposta de 0.0.0.0: bytes=32 tempo=675ms TTL=55
Resposta de 0.0.0.0: bytes=32 tempo=625ms TTL=55
Resposta de 0.0.0.0: bytes=32 tempo=1910ms TTL=55
Resposta de 0.0.0.0: bytes=32 tempo=2523ms TTL=55
Resposta de 0.0.0.0: bytes=32 tempo=629ms TTL=55
Resposta de 0.0.0.0: bytes=32 tempo=797ms TTL=55
Resposta de 0.0.0.0: bytes=32 tempo=1234ms TTL=55
Resposta de 0.0.0.0: bytes=32 tempo=728ms TTL=55
Resposta de 0.0.0.0: bytes=32 tempo=792ms TTL=55
Resposta de 0.0.0.0: bytes=32 tempo=580ms TTL=55
Resposta de 0.0.0.0: bytes=32 tempo=595ms TTL=55
Resposta de 0.0.0.0: bytes=32 tempo=671ms TTL=55
Resposta de 0.0.0.0: bytes=32 tempo=1460ms TTL=55
Resposta de 0.0.0.0: bytes=32 tempo=529ms TTL=55
Resposta de 0.0.0.0: bytes=32 tempo=760ms TTL=55
Resposta de 0.0.0.0: bytes=32 tempo=1287ms TTL=55
Resposta de 0.0.0.0: bytes=32 tempo=2077ms TTL=55
Resposta de 0.0.0.0: bytes=32 tempo=619ms TTL=55
Resposta de 0.0.0.0: bytes=32 tempo=1163ms TTL=55
Resposta de 0.0.0.0: bytes=32 tempo=1071ms TTL=55
Resposta de 0.0.0.0: bytes=32 tempo=717ms TTL=55
Resposta de 0.0.0.0: bytes=32 tempo=807ms TTL=55
Resposta de 0.0.0.0: bytes=32 tempo=520ms TTL=55
Resposta de 0.0.0.0: bytes=32 tempo=600ms TTL=55
Resposta de 0.0.0.0: bytes=32 tempo=670ms TTL=55
Resposta de 0.0.0.0: bytes=32 tempo=749ms TTL=55
Resposta de 0.0.0.0: bytes=32 tempo=825ms TTL=55
Resposta de 0.0.0.0: bytes=32 tempo=904ms TTL=55
Resposta de 0.0.0.0: bytes=32 tempo=2944ms TTL=55
Resposta de 0.0.0.0: bytes=32 tempo=2006ms TTL=55

Estatísticas de Ping para 0.0.0.0:
Pacotes: Enviados = 164, Recbidos = 160, Perdidos = 4 (2% de perda).
Aproximar um número redondo de vezes em milissegundos:
Mínimo = 500ms, Máximo = 3235ms, Média = 1055ms
Control-C
C:\Windows\System32\cmd -h

Interface: 10.29.37.50 --- 0x13
Endereço IP Endereço físico Tipo
10.29.37.49 00-20-0e-10-92-1d dinâmico
10.29.37.55 ff-ff-ff-ff-ff-ff estático
224.0.0.2 01-00-5e-00-00-02 estático
224.0.0.251 01-00-5e-00-00-7b estático
224.0.0.252 01-00-5e-00-00-7c estático
239.255.255.250 01-00-5e-7f-ff-fa estático
255.255.255.255 ff-ff-ff-ff-ff-ff estático

C:\Windows\System32\cmd -h PER 22065717-PI E.R CANDIDO PEREIRA DO LAGO- REDENÇÃO DO GURGUETA-PI
```