

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Wallace Teixeira


Cliente: Vivo

Empresa
EMC Brasil

VSAT-ID
VIVO-PER-27018687-AL

Link kbps
256K/128K

Plataforma
VSAT



```
# dvb tx show
```

Satellite (DVB) TX Configuration

```
-----
Auto start           : Enabled
IDU Output Power     : -19 dBm
IDU Max Output Power : 0.0 dBm
ODU Output Power     : 34.0 dBm
EIRP                 : 47.0 dBW
Default CW Frequency: 0.000000 GHz
ATM mode             : VC-Mux
Header Compression   : None
```

Satellite (DVB) Transmitter Status

```
-----
State                : On (DVB-RCS2)
IDU Output Power     : -19.9 dBm
ODU Output Power     : 33.9 dBm
EIRP                 : 46.9 dBW
```

Es/No : 12.0 dB
Header Compression : Disabled
Timing correction : -19 us (251034 us)
Frequency correction: -80 Hz
dvb rx show

Satellite (DVB) RX Configuration

Auto start : Enabled
Max Traffic MODCOD : 23 16APSK-9/10
RX watchdog : 15 minute

Idx	Pri	SymbRate[Msp/s]	Freq[GHz]	Mode	PopId	SatId	Pos	SatName
Name		Enable						
0	0	15.000000	12.059000	DVB-S2	102	0	0.0 E	
Yes								
1	1	9.320000	12.055825	DVB-S2	4	0	0.0 E	
No								
* 6	6	25.333333	12.050000	DVB-S2	102	0	0.0 E	
Yes								
7	7	30.000000	12.050000	DVB-S2	102	0	0.0 E	
Yes								

Satellite (DVB) Receiver Status

Rx State : On
DVB State : Forward link up
Network : 1326, T14R Beam
Frequency : 12.050021 GHz
Symbol Rate : 25.333074 Msp/s
S2 ModCod
 - receiving : 12 8PSK-3/5
 - current max : 20 16APSK-4/5
Pilot : On
Frame length : Short
DVB S2 Mode : ACM
DVB S2 Stream type : MPEG-TS
Roll off : 0.20
SNR : 14.1 dB
Input Power : -25 dBm

SatLink VSAT

10.29.47.49/wmi/dwp/index_page.dwp

STM

SatLink VSAT

Status

Satellite

Statistics

Device

DHCP

Eventlog

Configuration

Satellite

IP

Static NAT

Lineup

Device

Help

Introduction

Status

Configuration

Device Status

Model

Software Version

LAN MAC Address

DVB MAC Address

System Up Time

CPU Load

System Name

System Contact

System Location

ODU Serial Number

ODU HW Version

SatLink 2000

16.0.1.57

00:20:0e:10:58:76

00:20:0e:10:58:76

0 days, 00:04:41

15%

VIVO-PER-27018687-AL

Feira Grande - AL

104804040203090702520000

4.2

You are logged in as install (2)

© Copyright 2006-2014 STM Group. All Rights Reserved.

cmd - Atalho

Resposta de 8.8.8.8: bytes=32 tempo=562ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=661ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=661ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=593ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=584ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=634ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=580ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=656ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=616ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=581ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=610ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=621ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=575ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=657ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=610ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=576ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=647ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=611ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=567ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=553ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=682ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=682ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=636ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=599ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=599ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=641ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=590ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=605ms TTL=44

Estatísticas do Ping para 8.8.8.8:
Pacotes: Enviados = 116, Recebidos = 116, Perdidos = 0 (0% de perda).
Aproximar um número redondo de vezes em milissegundos:
Mínimo = 553ms, Máximo = 3548ms, Média = 928ms
Control-C
^C
C:\Windows\System32>arp -a

Interface: 10.29.47.50 --- 0xb
Endereço IP Endereço físico Tipo
10.29.47.49 00-20-0e-10-58-76 dinâmico
10.29.47.55 ff-ff-ff-ff-ff-ff estático
224.0.0.2 01-00-5e-00-00-02 estático
224.0.0.22 01-00-5e-00-00-16 estático
224.0.0.251 01-00-5e-00-00-fb estático
224.0.0.252 01-00-5e-00-00-fc estático
224.0.0.253 01-00-5e-00-00-fd estático
226.178.217.5 01-00-5e-32-d9-05 estático
239.192.152.143 01-00-5e-00-20-8f estático
239.255.255.250 01-00-5e-7f-ff-fa estático
255.255.255.255 ff-ff-ff-ff-ff-ff estático

C:\Windows\System32>