


TERMO DE ACEITE TÉCNICO


Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Allan Santos Cliente: VIVO

 Empresa
 VSAT-ID
 Link kbps
 Plataforma

 EMC Brasil
 VIVO-PER-23103710-CE
 256/128
 VSAT





Satellite (DVB) RX Configuration

Auto start : Enabled

Max Traffic MODCOD : 23 16APSK-9/10

RX watchdog : 15 minute

ldx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName Name Enable

* 0 0 9.320000 Yes

Satellite (DVB) Receiver Status

-----Rx State : On

DVB State : Forward link up
Network : 1326, GlobalIP@Telstar-14R
Frequency : 12.056068 GHz Frequency : 12.056068 GHz Symbol Rate : 9.320159 Msps

S2 ModCod

- receiving : 15 8PSK-5/6 - current max : 16 8PSK-8/9

: On Pilot Frame length : Short DVB S2 Mode : ACM DVB S2 Stream type: MPEG-TS

Roll off : 0.20 SNR : 13.3 dB Input Power : -25 dBm

Satellite (DVB) TX Configuration

Auto start : Enabled IDU Output Power : -21 dBm IDU Max Output Power: 0.0 dBm ODU Output Power : 34.6 dBm : 45.5 dBW

Default CW Frequency: 14.125750 GHz

ATM mode : VC-Mux Header Compression: None

Satellite (DVB) Transmitter Status

State : On (DVB-RCS) IDU Output Power : -21.1 dBm ODU Output Power : 35.1 dBm EIRP : 46.0 dBW Es/No : 12.0 dB

Header Compression: Disabled Timing correction : -146 us (260725 us)

Frequency correction: 110 Hz

ping 8.8.8.8

64 bytes from 8.8.8.8: time=690 ms 64 bytes from 8.8.8.8: time=1300 ms 64 bytes from 8.8.8.8: time=700 ms 64 bytes from 8.8.8.8: time=570 ms 64 bytes from 8.8.8.8: time=650 ms

--- ping statistics ---

5 packets transmitted, 5 received, 0.00 percent packet loss

rtt min/avg/max = 570/780/1300 ms