

TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Hernan Martins Alves Cliente: VIVO

> VSAT-ID Empresa Link kbps Plataforma EMC Brasil VIVO-PER- 31024392-MG 256/128 VSAT



Satellite (DVB) RX Configuration

Auto start

Max MODCOD : 23 16APSK-9/10 (SNR threshold: 23.5 dB)

RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId Sat[Id/Pos] Enable * 0 0 9.320000 12.055825 DVB-S2 4 0/ 0.0 E Yes

Satellite (DVB) Receiver Status

: On Rx State

DVB State : Forward link up

Network : 1326, GlobalIP@Telstar-14R

Frequency : 12.055824 GHz

Symbol Rate : 9.320026 Msps

S2 ModCod

- receiving : 16 8PSK-8/9 - current max : 16 8PSK-8/9

: On Pilot Frame length
DVB S2 Mode : Short DVB S2 Mode : ACM : 0.25 Roll off : 13.2 dB : -33 dBm SNR Input Power

Satellite (DVB) TX Configuration _____ : Enabled Auto start

```
IDU Output Power
                  : -20 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : 36.1 dBm
                   : 47.0 dBW
EIRP
Default CW Frequency: 0.000000 GHz
ATM mode : VC-Mux
Header Compression : None
Satellite (DVB) Transmitter Status
______
                   : On (DVB-RCS)
: On (DVB-1
IDU Output Power : -14.3 dBm
ODU Output Power : 34.8 dBm
State
EIRP
                    : 45.7 dBW
Eb/No
                    : 13.5 dB
Header Compression : Disabled
Timing correction : -297 us (261768 us)
Frequency correction: -260 Hz
IP DVB 10.53.0.189/32
Pinging 10.53.0.189 with 32 bytes of data:
Reply from 10.53.0.189: bytes=32 time=1670ms TTL=61
Reply from 10.53.0.189: bytes=32 time=732ms TTL=61
Reply from 10.53.0.189: bytes=32 time=647ms TTL=61
Reply from 10.53.0.189: bytes=32 time=760ms TTL=61
Reply from 10.53.0.189: bytes=32 time=553ms TTL=61
Reply from 10.53.0.189: bytes=32 time=578ms TTL=61
Reply from 10.53.0.189: bytes=32 time=676ms TTL=61
Reply from 10.53.0.189: bytes=32 time=597ms TTL=61
Reply from 10.53.0.189: bytes=32 time=695ms TTL=61
Reply from 10.53.0.189: bytes=32 time=608ms TTL=61
Reply from 10.53.0.189: bytes=32 time=713ms TTL=61
Reply from 10.53.0.189: bytes=32 time=625ms TTL=61
Reply from 10.53.0.189: bytes=32 time=542ms TTL=61
Reply from 10.53.0.189: bytes=32 time=634ms TTL=61
Reply from 10.53.0.189: bytes=32 time=552ms TTL=61
Reply from 10.53.0.189: bytes=32 time=558ms TTL=61
Ping statistics for 10.53.0.189:
   Packets: Sent = 16, Received = 16, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
   Minimum = 542ms, Maximum = 1670ms, Average = 696ms
# ping 8.8.8.8
64 bytes from 8.8.8.8: time=570 ms
64 bytes from 8.8.8.8: time=660 ms
64 bytes from 8.8.8.8: time=1450 ms
64 bytes from 8.8.8.8: time=580 ms
64 bytes from 8.8.8.8: time=530 ms
--- ping statistics ---
5 packets transmitted, 5 received, 0.00 percent packet loss
rtt min/avg/max = 530/750/1450 ms
```