


## **TERMO DE ACEITE TÉCNICO**

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Guilherme Cunha Cliente: VIVO

 Empresa
 VSAT-ID
 Link kbps
 Plataforma

 EMC Brasil
 VIVO-PER-24002763-RN
 256k/128k
 VSAT



## Satellite (DVB) TX Configuration

-----

Auto start : Enabled IDU Output Power : -15 dBm IDU Max Output Power: 0.0 dBm ODU Output Power : max EIRP : max

Default CW Frequency: 0.000000 GHz

ATM mode : VC-Mux Header Compression : None

## Satellite (DVB) Transmitter Status

State : On (DVB-RCS2)

IDU Output Power : -15.3 dBm
ODU Output Power : 35.7 dBm
EIRP : 49.0 dBW
Es/No : 11.0 dB
Header Compression : Disabled

Timing correction : -28 us (250299 us)

Frequency correction: -110 Hz

Satellite (DVB) RX Configuration

\_\_\_\_\_

Auto start : Enabled

Max Traffic MODCOD : 23 16APSK-9/10

RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName Name

Enable

\* 0 0 25.333333 12.050000 DVB-S2 102 0 0.0 E

Yes

1 1 30.000000 12.050000 DVB-S2 4 0 0.0 E

Yes

Satellite (DVB) Receiver Status

Rx State : On

DVB State : Forward link up
Network : 1326, T14R Beam
Frequency : 12.050163 GHz
Symbol Rate : 25.332934 Msps

S2 ModCod

- receiving : 12 8PSK-3/5 - current max : 22 16APSK-8/9

Pilot : On
Frame length : Short

DVB S2 Mode : ACM

DVB S2 Stream type : MPEG-TS

Roll off : 0.20

SNR : 15.6 dB

Input Power : -26 dBm

