


TERMO DE ACEITE TÉCNICO



```
ODU Output Power : 34.6 dBm
EIRP : 47.9 dBW Eb/No : 15.0 dB
Header Compression : Disabled
Timing correction : -107 us (261652 us)
Frequency correction: -300 Hz
# dvb rx show
Satellite (DVB) RX Configuration
-----
Auto start : Enabled

Max MODCOD : 23 16APSK-9/10 (SNR threshold: 23.5 dB)

RX watchdog : 15 minute
Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId Enable
* 0 0 9.320000 12.055825 DVB-S2 4 Yes
Satellite (DVB) Receiver Status
_____
           : On
: Forward link up
: 1326, GlobalIPO
Rx State
DVB State
                   : 1326, GlobalIP@Telstar-14R
Network
Frequency : 12.055696 GHz
Symbol Rate : 9.319939 Msps
S2 ModCod
  - receiving : 14 8PSK-3/4
     - current max : 23 16APSK-9/10
              : On
Pilot
Frame length : Short DVB S2 Mode : ACM
DVB S2 Mode
                   : ACM
Roll off
                   : 0.25
SNR : 14.4 dB
Input Power : -33 dBm
IP DVB 10.50.0.25/32
Ping desde o MGMT- Server ao IP de trafego e para o DVB.
Ping desde dentro da VSAT 8.8.8.8
# ping 8.8.8.8
64 bytes from 8.8.8.8: time=770 ms
64 bytes from 8.8.8.8: time=610 ms
64 bytes from 8.8.8.8: time=630 ms
64 bytes from 8.8.8.8: time=560 ms
64 bytes from 8.8.8.8: time=700 ms
--- 8.8.8.8 ping statistics ---
5 packets transmitted, 5 received, 0.00 percent packet loss
rtt min/avg/max = 560/650/770 ms
```