

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Bruno Carvalho de Sá


Cliente: VIVO

Empresa
EMC Brasil

VSAT-ID
VIVO-PER-26078635-PE

Link kbps
256/128

Plataforma
VSAT



```
# dvb tx show
```

Satellite (DVB) TX Configuration

```
-----
Auto start           : Enabled
IDU Output Power     : -22 dBm
IDU Max Output Power : 0.0 dBm
ODU Output Power     : 33.2 dBm
EIRP                 : 46.5 dBW
Default CW Frequency: 14.125850 GHz
ATM mode             : VC-Mux
Header Compression   : None
```

Satellite (DVB) Transmitter Status

```
-----
State                : On (DVB-RCS)
IDU Output Power     : -24.8 dBm
ODU Output Power     : 33.3 dBm
EIRP                 : 46.6 dBW
Es/No                : 14.0 dB
Header Compression   : Disabled
Timing correction    : -240 us (262271 us)
Frequency correction : -20 Hz
```

```
# dvb rx show
```

Satellite (DVB) RX Configuration

Auto start : Enabled
Max Traffic MODCOD : 23 16APSK-9/10
RX watchdog : 15 minute

Idx	Pri	SymbRate[Mbps]	Freq[GHz]	Mode	PopId	SatId	Pos	SatName	Name
Enable									
* 0	0	9.320000	12.055825	DVB-S2	102	0	0.0 E		
Yes									

Satellite (DVB) Receiver Status

Rx State : On
DVB State : Forward link up
Network : 1326, GlobalIP@Telstar-14R
Frequency : 12.056056 GHz
Symbol Rate : 9.320129 Msps
S2 ModCod
- receiving : 15 8PSK-5/6
- current max : 16 8PSK-8/9
Pilot : On
Frame length : Short
DVB S2 Mode : ACM
DVB S2 Stream type : MPEG-TS
Roll off : 0.20
SNR : 13.6 dB
Input Power : -28 dBm

ping 8.8.8.8

64 bytes from 8.8.8.8: time=940 ms
64 bytes from 8.8.8.8: time=640 ms
64 bytes from 8.8.8.8: time=760 ms
64 bytes from 8.8.8.8: time=700 ms
64 bytes from 8.8.8.8: time=720 ms

--- ping statistics ---

5 packets transmitted, 5 received, 0.00 percent packet loss
rtt min/avg/max = 640/950/1940 ms



