


TERMO DE ACEITE TÉCNICO

Solicitante: SES - Secretaria de Estado de Saúde de Minas Gerais

NOC/Operadora: Pedro Henrique da R. Bernardes Operadora/Cliente: Walter Leandro

GRE/Prodemge: Douglas Alvares Responsável/cliente: Cintia Caldas

ConsórcioVSAT-IDPorta kbpsPlataformaSTM/VodanetSES-SAOS-3597384/153VSAT



Satellite (DVB) RX Configuration

Auto start : Enabled

Max MODCOD: 15 8PSK-5/6 (SNR threshold: 10.6 dB)

ACM Latency : On

RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId Enable

* 0 0 13.333000 11.588250 DVB-S2 2 Yes

1 1 0.000000 0.000000 DVB-S2 2 Yes

Satellite (DVB) Receiver Status

Rx State : On

DVB State : Forward link up

Network : 65281, Prodemge@Vodanet

Frequency: 11.588454 GHz Symbol Rate: 13.332941 Msps

S2 ModCod

- receiving : 4 QPSK-1/2
- current max : 15 8PSK-5/6

Pilot : On

Frame length : Short frame

DVB S2 Mode : ACM Roll off : 0.25 SNR : 12.1 dB

Input Power: -35 dBm

```
Satellite (DVB) TX Configuration
Auto start : Enabled
IDU output power : -22 dBm
IDU max output power: 0.0 dBm
EIRP : max
Default CW Frequency: 0.000000 GHz
ATM mode : VC-Mux
Header Compression : UDP/IP/DSM-CC
Satellite (DVB) Transmitter Status
______
State : On (TDMA)
IDU Output Power: -18.7 dBm
ODU Output Power: 34.5 dBm
EIRP: 48.0 dBW
Es/No : 13.5 dB
Header Compression : DSM-CC
Timing correction: 25 us (260283 us)
Frequency correction: -90 Hz
IP DVB: 10.148.2.134/32
C:\>ping -n 10 10.145.241.1
Pinging 10.145.241.1 with 32 bytes of data:
Reply from 10.145.241.1: bytes=32 time=572ms TTL=62
Reply from 10.145.241.1: bytes=32 time=592ms TTL=62
Reply from 10.145.241.1: bytes=32 time=607ms TTL=62
Reply from 10.145.241.1: bytes=32 time=623ms TTL=62
Reply from 10.145.241.1: bytes=32 time=546ms TTL=62
Reply from 10.145.241.1: bytes=32 time=557ms TTL=62
Reply from 10.145.241.1: bytes=32 time=578ms TTL=62
Reply from 10.145.241.1: bytes=32 time=588ms TTL=62
Reply from 10.145.241.1: bytes=32 time=609ms TTL=62
Reply from 10.145.241.1: bytes=32 time=619ms TTL=62
Ping statistics for 10.145.241.1:
Packets: Sent = 10, Received = 10, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
Minimum = 546ms, Maximum = 623ms, Average = 589ms
```