


## TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Leonardo Martins Cliente: VIVO

 Empresa
 VSAT-ID
 Link kbps
 Plataforma

 EMC Brasil
 VIVO-PER-27008185-AL
 256k/128k
 VSAT



# dvb tx show

Satellite (DVB) TX Configuration

\_\_\_\_\_

Auto start : Enabled
IDU Output Power : -17 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : 33.2 dBm
EIRP : 46.5 dBW
Default CW Frequency: 0.000000 GHz

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

State : On (DVB-RCS)

IDU Output Power : -15.9 dBm

ODU Output Power : 27.0 dBm

EIRP : 40.3 dBW

Es/No : 12.0 dB

Header Compression : Disabled

Timing correction : -148 us (261817 us)

Frequency correction: -110 Hz

# dvb rx show

Satellite (DVB) RX Configuration -----

Auto start : Enabled
Max Traffic MODCOD : 23 16APSK-9/10
RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName Name

Enable

\* 0 0 9.320000 12.055825 DVB-S2 102 0 0.0 E

Yes

Satellite (DVB) Receiver Status \_\_\_\_\_

Rx State : On
DVB State : Forward link up : 1326, T14R Beam Network Frequency : 12.055778 GHz
Symbol Rate : 9.319981 Msps

S2 ModCod

- receiving : 14 8PSK-3/4 - current max : 16 8PSK-8/9

: On
Frame length : Short
DVB S2 Mode : ACM
DVB S2 S+--DVB S2 Stream type : MPEG-TS Roll off : 0.20 SNR : 13.1 dB Input Power : -27 dBm

```
atísticas de Ping para 8.8.9.8:
Pacotes: Emriados - 359, Recebidos - 259, Perdidos - 8 (8: de
pareda).
        ur um número redundo de vezez en milizzegundes:
ma - 513ms. Máximo - 2326my. Mádia - 697ms
Windows\System32>W1WO-PER 27088:85-AL E.M.I.F SAMIA ANA — SÃO JOSÉ DA TAPERA-
CO JOSÉ DA TAPERA-AL.
```