

## **TERMO DE ACEITE TÉCNICO**

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Bruno Carvalho de Sá Cliente: VIVO

 Empresa
 VSAT-ID
 Link kbps
 Plataforma

 EMC Brasil
 VIVO-PER-23167360-CE
 256/128
 VSAT



Satellite (DVB) TX Configuration

-----

Auto start : Enabled
IDU Output Power : -15 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : 34.7 dBm
EIRP : 48.0 dBW
Default CW Frequency: 0.000000 GHz

ATM mode : VC-Mux Header Compression : None

## Satellite (DVB) Transmitter Status

\_\_\_\_\_

State : On (TDMA)

IDU Output Power : -25.1 dBm

ODU Output Power : 34.7 dBm

EIRP : 48.0 dBW

Eb/No : 13.0 dB

Header Compression : Disabled

Timing correction : -22 us (260014 us)

Frequency correction: -540 Hz

# dvb rx show

Satellite (DVB) RX Configuration

Auto start : Enabled

Max MODCOD : 23 16APSK-9/10 (SNR threshold: 23.5 dB)

RX watchdog : 15 minute

```
Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId Enable
* 0 0 9.320000 12.055825 DVB-S2 4 Yes
Satellite (DVB) Receiver Status
______
Rx State : On

DVB State : Forward link up

Network : 1326, GlobalIP@Telstar-14R

Frequency : 12.055380 GHz

Symbol Rate : 9.319834 Msps
S2 ModCod
 - receiving : 1 QPSK-1/4
- current max : 23 16APSK-9/10
Pilot : On
Frame length : Short
DVB S2 Mode : ACM
Roll off : 0.25
SNR : 14.7 dB
Input Power : -23 dBm
# ping 8.8.8.8
64 bytes from 8.8.8.8: time=650 ms
64 bytes from 8.8.8.8: time=700 ms
64 bytes from 8.8.8.8: time=680 ms
64 bytes from 8.8.8.8: time=630 ms
64 bytes from 8.8.8.8: time=740 ms
--- 8.8.8.8 ping statistics ---
5 packets transmitted, 5 received, 0.00 percent packet loss
rtt min/avg/max = 630/670/740 ms
```