

TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Rogério Momi Frias Cliente: VIVO

 Empresa
 VSAT-ID
 Link kbps
 Plataforma

 EMC Brasil
 VIVO-PER- 35299315-SP
 256/128
 VSAT



Satellite (DVB) RX Configuration

Auto start : Enabled

Auto start : Enabled

Max Traffic MODCOD : 23 16APSK-9/10

RX watchdog : 15 minute

ldx Pri SymbRate[Msps] Freq[GHz] Mode Popld SatId Pos SatName Name Enable

* 0 0 15.000000 12.059000 DVB-S2 102 0 0.0 E Yes 1 1 9.320000 12.055825 DVB-S2 4 0 0.0 E Yes

Satellite (DVB) Receiver Status

Rx State : On

DVB State : Forward link up Network : 1326, T14R Beam Frequency : 12.059124 GHz Symbol Rate : 14.999904 Msps

S2 ModCod

- receiving : 19 16APSK-3/4 - current max : 20 16APSK-4/5

Pilot : On

Frame length : Short DVB S2 Mode : ACM

DVB S2 Stream type: MPEG-TS

Roll off : 0.20 SNR : 14.3 dB Input Power : -26 dBm

Satellite (DVB) TX Configuration

Auto start : Enabled IDU Output Power : -22 dBm IDU Max Output Power: 0.0 dBm ODU Output Power : 33.7 dBm

EIRP : 47.0 dBW

Default CW Frequency: 0.000000 GHz

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

State : On (DVB-RCS2) IDU Output Power : -17.5 dBm ODU Output Power : 33.3 dBm

EIRP : 46.6 dBW Es/No :12.5 dB

Header Compression: Disabled Timing correction: -92 us (255063 us)

Frequency correction: 40 Hz

```
Resporta de 8.8.8.8: bytes=32 tempo=863ms TIL=55
Resporta de 8.8.8.8: bytes=32 tempo=767ms TIL=55
Resporta de 8.8.8.8: bytes=32 tempo=767ms TIL=55
Resporta de 8.8.8.8: bytes=32 tempo=767ms TIL=55
Resporta de 8.8.8.8: bytes=32 tempo=727ms TIL=55
Resporta de 8.8.8.8: bytes=32 tempo=527ms TIL=55
Resporta de 8.8.8.8: bytes=32 tempo=527ms TIL=55
Resporta de 8.8.8.8: bytes=32 tempo=527ms TIL=55
Resporta de 8.8.8.8: bytes=32 tempo=679ms TIL=55
Resporta de 8.8.8.8: bytes=32 tempo=679ms TIL=55
Resporta de 8.8.8.8: bytes=32 tempo=679ms TIL=55
Resporta de 8.8.8.8: bytes=32 tempo=676ms TIL=55
Resporta de 8.8.8.8: bytes=32 tempo=678ms TIL=55
Resporta de 8.8.8.8: bytes=32 tempo=776ms TIL=55
Resporta de 8.8.8.8: bytes=32 tempo=776ms TIL=55
Resporta de 8.8.8.8: bytes=32 tempo=676ms TIL=55
Resporta de 8.8.8.8: bytes=32 tempo=6
```