

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Rogério Momi Frias


Cliente: VIVO

Empresa
EMC Brasil

VSAT-ID
VIVO-PER-24011649-RN

Link kbps
256/128

Plataforma
VSAT



Satellite (DVB) RX Configuration

Auto start : Enabled
Max MODCOD : 23 16APSK-9/10 (SNR threshold: 23.5 dB)
RX watchdog : 15 minute

Idx	Pri	SymbRate[Mbps]	Freq[GHz]	Mode	PopId	Enable
* 0	0	9.320000	12.055825	DVB-S2 4		Yes

Satellite (DVB) Receiver Status

Rx State : On
DVB State : Forward link up
Network : 1326, GlobalIP@Telstar-14R
Frequency : 12.055839 GHz
Symbol Rate : 9.319991 Msps
S2 ModCod
- receiving : 15 8PSK-5/6
- current max : 23 16APSK-9/10
Pilot : On
Frame length : Short
DVB S2 Mode : ACM
Roll off : 0.25
SNR : 13.8 dB
Input Power : -24 dBm

Satellite (DVB) TX Configuration

Auto start : Enabled
IDU Output Power : -30 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : 34.7 dBm
EIRP : 48.0 dBW
Default CW Frequency: 0.000000 GHz
ATM mode : VC-Mux
Header Compression : None

Satellite (DVB) Transmitter Status

State : On (TDMA)
IDU Output Power : -16.9 dBm
ODU Output Power : 35.2 dBm
EIRP : 48.5 dBW
Eb/No : 14.5 dB
Header Compression : Disabled
Timing correction : -247 us (261794 us)
Frequency correction: -40 Hz

ping 8.8.8.8

64 bytes from 8.8.8.8: time=740 ms
64 bytes from 8.8.8.8: time=540 ms
64 bytes from 8.8.8.8: time=540 ms
64 bytes from 8.8.8.8: time=560 ms
64 bytes from 8.8.8.8: time=560 ms

--- 8.8.8.8 ping statistics ---

5 packets transmitted, 5 received, 0.00 percent packet loss
rtt min/avg/max = 540/580/740 ms