

TERMO DE ACEITE TÉCNICO

Solicitante: Global Eagle

NOC/Operador: Jefferson de Souza Marques Cliente: SEE

 Empresa
 VSAT-ID
 Link kbps
 Plataforma

 Global Eagle
 SEE-AC-REINALDO_PEREIRA
 2M/512k – 1/4
 VSAT



#

System Information:

Name : SEE-AC-REINALDO_PEREIRA

Location : Rio Branco - Acre Contact :

System Up time : 2 days, 21:59:22

CPU Load : 23%

System time (UTC) : 15 December 2017 17:34:40

Broadcast Message : not set

HW:

Model : SatLink 2000 HW ID : 120033 Main board ID : 120026 R6.2

MAC addresses:

Ethernet (LAN) : 00:20:0e:10:5c:ce Satellite (DVB) : 00:20:0e:10:5c:ce

```
Satellite (DVB) RX Configuration
-----
Auto start : Enabled
Max Traffic MODCOD : 23 16APSK-9/10
               : 15 minute
RX watchdog
Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName
                                                                             Name
Enable
                                                  0 0.0 E
* 6 6
         25.333333
                      12.050000 DVB-S2 4
Yes
                                             0 0.0 E
7 7 30.000000 12.050000 DVB-S2 4
Yes
Satellite (DVB) Receiver Status
Rx State
           : On
                  : Forward link up
DVB State
Network : 1326, T14R Beam Frequency : 12.050069 GHz Symbol Rate : 25.332859 Msps
S2 ModCod
 - receiving : 13 8PSK-2/3
     - current max : 18
                         16APSK-2/3
              : On
: Short
: ACM
Pilot
Frame length
DVB S2 Mode
DVB S2 Stream type : MPEG-TS
Roll off : 0.20
SNR : 12.0 dB
Input Power : -36 dBm
Satellite (DVB) TX Configuration
Auto start : Enabled IDU Output Power : -20 dBm
IDU Max Output Power: 0.0 dBm
Default CW Frequency: 0.000000 GHz
ATM mode : VC-Mux Header Compression : None
Satellite (DVB) Transmitter Status
State : On (DVB-RCS)
IDU Output Power : -20.0 dBm
Es/No : 12.5 dB
Header Compression : Disabled
```

Timing correction : -161 us (246166 us)

Frequency correction: 90 Hz

#