

## **TERMO DE ACEITE TÉCNICO**

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Bruno Carvalho de Sá Cliente: VIVO

EmpresaVSAT-IDLink kbpsPlataformaEMC BrasilVIVO-PER-22003584-PI256/128VSAT



## # dvb tx show

## Satellite (DVB) TX Configuration

Auto start : Enabled

IDU Output Power : -20 dBm IDU Max Output Power: 0.0 dBm

Default CW Frequency: 14.162500 GHz

ATM mode : VC-Mux Header Compression : None

## Satellite (DVB) Transmitter Status

-----

State : On (DVB-RCS)
IDU Output Power : -20.1 dBm
Es/No : 12.0 dB
Header Compression : Disabled

Timing correction : -324 us (259716 us)

Frequency correction: 20 Hz

# dvb rx show

Satellite (DVB) RX Configuration

Auto start

Auto start : Enabled
Max Traffic MODCOD : 23 16APSK-9/10
RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName Name

Enable

9.320000 12.055825 DVB-S2 102 0 0.0 E \* 0 0

Yes

Satellite (DVB) Receiver Status

\_\_\_\_\_

Rx State : On

DVB State : Forward link up

Network : 1326, T14R Beam

Frequency : 12.055906 GHz

Symbol Rate : 9.320076 Msps

S2 ModCod

- receiving : 15 8PSK-5/6 - current max : 16 8PSK-8/9

rilot : On
Frame length : Short
DVB S2 Mode : ACM
DVB S2 Stroom DVB S2 Stream type : MPEG-TS Roll off : 0.20 SNR : 14.8 dB Input Power : -36 dBm

IP DVB 172.18.131.166 /32