

# TERMO DE ACEITE TÉCNICO

**Solicitante:** VIVO- Projeto Escolas Rurais

**NOC/Operador:** Leonardo Martins

**Cliente:** VIVO

**Empresa**  
EMC Brasil

**VSAT-ID**  
VIVO-PER-270183770-AL

**Link kbps**  
256k/128k

**Plataforma**  
VSAT



Terminet 10.29.46.49

Header Compression : None

**Satellite <DVB> Transmitter Status**

State : On <DVB-RCS2>  
 IDU Output Power : -17.9 dBm  
 ODU Output Power : 28.9 dBm  
 EIRP : 41.9 dBW  
 EIRP/No : 14.0 dB  
 Header Compression : Disabled  
 Timing correction : 4 us <255507 us>  
 Frequency correction: 270 Hz

**Satellite <DVB> RX Configuration**

Auto start : Enabled  
 Max Traffic MODCOD : 23 16APSK-9/10  
 RX watchdog : 15 minute

| Idx | Pri | SymbRate[Mbps] | Freq[GHz] | Mode       | PopId | SatId | Pos   | S |
|-----|-----|----------------|-----------|------------|-------|-------|-------|---|
| 0   | 0   | 15.000000      | 12.059000 | DVB-S2 102 | 0     | 0     | 0.0 E |   |
| 1   | 1   | 9.320000       | 12.055025 | DVB-S2 4   | 0     | 0     | 0.0 E |   |

**Satellite <DVB> Receiver Status**

Rx State : On  
 DVB State : Forward link up  
 Network : 1326, T14R Beam  
 Frequency : 12.059007 GHz  
 Symbol Rate : 15.000036 Mbps  
 S2 ModCod :  
   - receiving : 12 8PSK-3/5  
   - current max : 22 16APSK-8/9  
 Pilot : On  
 Frame length : Short  
 DVB S2 Mode : ACM  
 DVB S2 Stream type : MPEG-TS  
 Roll off : 0.20  
 SNR : 15.6 dB

SatLink VSAT

10.29.46.49/wmi/dwp/index\_page.dwp



**Status**

Satellite Statistics

Device DHCP Eventlog

**Configuration**

Satellite IP Static NAT Lineup Device Help Introduction

**Device Status**

Model: SatLink 2000

Software Version: 16.0.1.57

LAN MAC Address: 00:20:0e:10:84:e9

DVB MAC Address: 00:20:0e:10:84:e9

System Up Time: 0 days, 00:05:54

CPU Load: 17%

System Name: VIVO-PER-270183770-AL

System Contact:

System Location: FEIRA GRANDE - AL

ODU Serial Number: 104804040203090213300000


You are logged in as install (2)

© Copyright 2006-2014 STM Group. All Rights Reserved.

PT 18:27 23/06/2017

SatLink VSAT

10.29.46.49/wmi/dwp/index\_page.dwp



**Status**

Satellite Statistics

Device DHCP Eventlog

**Configuration**

Satellite IP Static NAT Lineup Device Help Introduction Status Configuration

**Device Status**

Model: SatLink 2000

Software Version: 16.0.1.57

LAN MAC Address: 00:20:0e:10:84:e9

DVB MAC Address: 00:20:0e:10:84:e9

System Up Time: 0 days, 00:04:05

CPU Load: 18%

System Name: VIVO-PER-270183770-AL

System Contact:

System Location: FEIRA GRANDE - AL

ODU Serial Number: 104804040203090213300000

ODU HW Version: 4.2

You are logged in as install (2)

© Copyright 2006-2014 STM Group. All Rights Reserved.

cmd - Atalho

```

Resposta de 8.8.8.8: bytes=32 tempo=759ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=841ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1639ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=595ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1512ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1438ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1495ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1406ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1368ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=2398ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1683ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=909ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=896ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=632ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=720ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=572ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=716ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=572ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=802ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=617ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1196ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=572ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=663ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=573ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=602ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=563ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=2126ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1877ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=573ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1677ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=700ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=2355ms TTL=44

Estatísticas do Ping para 8.8.8.8:
Pacotes: Enviados = 63, Recebidos = 61, Perdidos = 2 (3% perda),
Aproximar um número redondo de vezes em milissegundos:
Mínimo = 563ms, Máximo = 2398ms, Média = 1006ms
Control-C
C:\Windows\System32>
          
```

PT 18:40 23/06/2017