

TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Leonardo Martins

Cliente: VIVO

Empresa
EMC Brasil

VSAT-ID
VIVO-PER-31083364-MG

Link kbps
256k/128k

Plataforma
VSAT



SatLink VSAT
10.29.43.81/wmi/dwp/index_page.dwp

Status
Satellite
Statistics
Device
DHCP
Eventlog
Configuration
Satellite
IP
Static NAT
Lineup
Device
Help
Introduction
Status
Configuration

Device Status
Model
SatLink 2000
Software Version
16.0.1.57
LAN MAC Address
00:20:0e:10:52:1a
DVB MAC Address
00:20:0e:10:52:1a
System Up Time
0 days, 00:27:22
CPU Load
13%
System Name
VIVO-PER-31083364-MG-TES
System Contact
System Location
Oihos dagua - MG
ODU Serial Number
104804040203090604240000
ODU HW Version
4.2

You are logged in as install (2)
© Copyright 2006-2014 STM Group. All Rights Reserved.

Telnet 10.29.43.81

Satellite (DVB) TX Configuration
Auto start : Enabled
IDB Output Power : -28 dBm
ODG Max Output Power : 0.0 dBm
ODG Output Power : 33.2 dBm
EIRP : 46.2 dBm
EIRP : 46.2 dBm
Default CW Frequency : 14.125750 GHz
STM mode : DC-Mux
Header Compression : None

Satellite (DVB) Transmitter Status
State : On (DVB-RCS2)
IDB Output Power : -21.8 dBm
ODG Output Power : 33.2 dBm
EIRP : 46.2 dBm
EIRP : 46.2 dBm
Header Compression : Disabled
Timing correction : -95 us (254635 us)
Frequency correction : -180 Hz

Satellite (DVB) RX Configuration
Auto start : Enabled
Max Traffic MODCOD : Enable
RX watchdog : 15 minutes

Idx Pri SynchRate[Hz] Prd[Hz] Freq[GHz] Mode PupId SatId Pos SatName
0 0 15.000000 12.859800 DVB-S2 182 0 0.0 E
Yes

Satellite (DVB) Receiver Status
Rx State : On
DVB State : Forward link up
Network : 1325 T-80 Beam
Frequency : 12.85885 GHz
Symbol Rate : 14.999951 Msps
E2 ModCod : ? QPSK-3/4
- receiving : 22 16APSK-8/9
- current max : 22 16APSK-8/9
Pilot : On
Frame length : Short
DVB E2 Mode : 80M
DVB E2 Stream type : MPEG-TS
Roll off : 0.20
SNR : 15.9 dB
Input Power : -28 dBm
B No Such Command
SV versions :
Boot : 14.0.1.19
Current : 16.0.1.57

SatLink VSAT
10.29.43.81/wmi/dwp/index_page.dwp

Status
Satellite
Statistics
Device
DHCP
Eventlog
Configuration
Satellite
IP
Static NAT
Lineup
Device
Help
Introduction
Status
Configuration

Device Status
Model
SatLink 2000
Software Version
16.0.1.57
LAN MAC Address
00:20:0e:10:52:1a
DVB MAC Address
00:20:0e:10:52:1a
System Up Time
0 days, 00:10:02
CPU Load
14%
System Name
VIVO-PER-31083364-MG
System Contact
System Location
Oihos dagua - MG
ODU Serial Number
106548040203080603350000
ODU HW Version
4.2

You are logged in as install (2)
© Copyright 2006-2014 STM Group. All Rights Reserved.

C:\Windows\system32\cmd.exe

Resposta de 8.8.8.8: bytes=32 tempo=2115ms TTL=43
Resposta de 8.8.8.8: bytes=32 tempo=1439ms TTL=43
Resposta de 8.8.8.8: bytes=32 tempo=711ms TTL=43
Resposta de 8.8.8.8: bytes=32 tempo=1862ms TTL=43
Resposta de 8.8.8.8: bytes=32 tempo=652ms TTL=43
Resposta de 8.8.8.8: bytes=32 tempo=852ms TTL=43
Resposta de 8.8.8.8: bytes=32 tempo=1295ms TTL=43
Resposta de 8.8.8.8: bytes=32 tempo=2127ms TTL=43
Resposta de 8.8.8.8: bytes=32 tempo=1475ms TTL=43
Resposta de 8.8.8.8: bytes=32 tempo=1426ms TTL=43
Resposta de 8.8.8.8: bytes=32 tempo=2175ms TTL=43
Resposta de 8.8.8.8: bytes=32 tempo=576ms TTL=43
Resposta de 8.8.8.8: bytes=32 tempo=798ms TTL=43
Resposta de 8.8.8.8: bytes=32 tempo=2415ms TTL=43
Resposta de 8.8.8.8: bytes=32 tempo=950ms TTL=43
Resposta de 8.8.8.8: bytes=32 tempo=899ms TTL=43
Resposta de 8.8.8.8: bytes=32 tempo=2176ms TTL=43
Resposta de 8.8.8.8: bytes=32 tempo=727ms TTL=43
Resposta de 8.8.8.8: bytes=32 tempo=1161ms TTL=43
Resposta de 8.8.8.8: bytes=32 tempo=718ms TTL=43
Resposta de 8.8.8.8: bytes=32 tempo=1372ms TTL=43
Resposta de 8.8.8.8: bytes=32 tempo=2432ms TTL=43
Resposta de 8.8.8.8: bytes=32 tempo=885ms TTL=43
Resposta de 8.8.8.8: bytes=32 tempo=951ms TTL=43
Resposta de 8.8.8.8: bytes=32 tempo=1372ms TTL=43
Resposta de 8.8.8.8: bytes=32 tempo=2432ms TTL=43
Resposta de 8.8.8.8: bytes=32 tempo=1180ms TTL=43
Resposta de 8.8.8.8: bytes=32 tempo=1505ms TTL=43
Resposta de 8.8.8.8: bytes=32 tempo=1465ms TTL=43
Resposta de 8.8.8.8: bytes=32 tempo=1779ms TTL=43
Resposta de 8.8.8.8: bytes=32 tempo=1884ms TTL=43
Resposta de 8.8.8.8: bytes=32 tempo=2099ms TTL=43
Resposta de 8.8.8.8: bytes=32 tempo=768ms TTL=43
Resposta de 8.8.8.8: bytes=32 tempo=1832ms TTL=43
Resposta de 8.8.8.8: bytes=32 tempo=1884ms TTL=43
Resposta de 8.8.8.8: bytes=32 tempo=1761ms TTL=43

Estatísticas de Ping para 8.8.8.8:
Pacotes: Enviados = 101, Recebidos = 101, Perdidos = 0 (0% de perda).
Aproximar um número redondo de vezes em milissegundos:
Mínimo = 561ms, Máximo = 2855ms, Média = 1146ms
Ctrl+C
C:\Users\DjIrmadez>arp -a
Interface: 192.168.1.189 --- 0xc
Endereço IP Endereço físico Tipo
192.168.1.254 00-11-97-8c-63-85 dinâmico
192.168.1.255 ff-ff-ff-ff-ff-ff estático
224.0.0.22 01-00-5e-00-00-16 estático
224.0.0.251 01-00-5e-00-00-1b estático
224.0.0.252 01-00-5e-00-00-1c estático
224.0.1.48 01-00-5e-00-01-3c estático
239.255.255.250 01-00-5e-7f-ff-ff-ff estático
255.255.255.255 ff-ff-ff-ff-ff-ff estático
C:\Users\DjIrmadez>