TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Rogério Momi Frias

Cliente: VIVO

Empresa	VSAT-ID	Link kbps	Plataforma
EMC Brasil	VIVO-PER-24006122-RN	256/128	VSAT

Satellite (DVB) RX Configuration

Auto start   : Enabled
Max MODCOD   : 23   16APSK-9/10 (SNR threshold: 23.5 dB)
RX watchdog   : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode   PopId Enable
* 0 0   9.320000   12.055825 DVB-S2 4   Yes

Satellite (DVB) Receiver Status

Rx State   : On
DVB State   : Forward link up
Network   : 1326, GlobalIP@Telstar-14R
Frequency   : 12.055896 GHz
Symbol Rate   : 9.319893 Msps
S2 ModCod
    - receiving : 16   8PSK-8/9
    - current max : 23   16APSK-9/10
Pilot   : On
Frame length   : Short
DVB S2 Mode   : ACM
Roll off   : 0.25
SNR   : 14.6 dB
Input Power   : -23 dBm

```
Satellite (DVB) TX Configuration
-------------------------------
Auto start       : Enabled
IDU Output Power   : -30 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power   : 34.7 dBm
EIRP           : 48.0 dBW
Default CW Frequency: 0.000000 GHz
ATM mode        : VC-Mux
Header Compression : None


Satellite (DVB) Transmitter Status
-------------------------------
State          : On (TDMA)
IDU Output Power   : -18.3 dBm
ODU Output Power   : 35.1 dBm
EIRP          : 48.4 dBW
Eb/No          : 14.0 dB
Header Compression : Disabled
Timing correction  : -164 us (261487 us)
Frequency correction: -40 Hz



ping 8.8.8.8
64 bytes from 8.8.8.8: time=520 ms
64 bytes from 8.8.8.8: time=710 ms
64 bytes from 8.8.8.8: time=540 ms
64 bytes from 8.8.8.8: time=540 ms
64 bytes from 8.8.8.8: time=570 ms

--- 8.8.8.8 ping statistics ---
5 packets transmitted, 5 received,  0.00 percent packet loss
rtt min/avg/max = 520/570/710 ms
```