

TERMO DE ACEITE TÉCNICO

Solicitante: PRODEMGE / SEE

NOC/Operadora: Pedro Bernardes Operadora/Cliente: Gilvan Junior

GRE/Prodemge: João Antinossi Responsável/cliente: Ronan Nunes Pereira

ConsórcioVSAT-IDPorta kbpsPlataformaEMC/VodanetSEE-SAES-222422MbpsVSAT



Satellite (DVB) RX Configuration
----Auto start : Enabled

Max Traffic MODCOD : 23 16APSK-9/10

RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName Name

Enable

* 0 0 4.883300 12.176420 DVB-S2 104 0 0.0 E

Yes

1 1 16.667000 11.962753 DVB-S2 2 0 0.0 E

Yes

Satellite (DVB) Receiver Status

Rx State : On

DVB State : Forward link up

Network : 65281, Prodemge@Vodanet

Frequency : 12.176316 GHz Symbol Rate : 4.882972 Msps

S2 ModCod

- receiving : 4 QPSK-1/2 - current max : 21 16APSK-5/6

Pilot : On
Frame length : Short

DVB S2 Mode : ACM

DVB S2 Stream type : MPEG-TS

Roll off : 0.20

SNR : 14.0 dB

Input Power : -32 dBm

```
# dvb tx show
Satellite (DVB) TX Configuration
_____
Auto start : Enabled IDU Output Power : -21 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : 33.5 dBm
                    : 46.5 dBW
Default CW Frequency: 0.000000 GHz
ATM mode : VC-Mux
Header Compression : UDP/IP
Satellite (DVB) Transmitter Status
-----
State : On (DVB-RCS2)
IDU Output Power : -17.4 dBm
ODU Output Power : 33.1 dBm
                    : 46.1 dBW
EIRP
                    : 13.0 dB
Es/No
Header Compression : Disabled - HC for RCS2 not supported by HUB
Timing correction : -362 us (281201 us)
Frequency correction: 130 Hz
# device show
System Information:
    Name
                        : SEE-SAES-22242
    Location
                        : S¦O JO¦O DAS MISS¦ES - MG
    Contact
    System Up time : 0 days, 01:17:43 CPU Load : 6%
    System time(UTC) : 29 October 2017 15:20:21
Broadcast Message : not set
HW:
    Model
                        : SatLink 2000
    HW ID
                        : 120033
    Main board ID
                        : 120026 R6.2
MAC addresses:
    Ethernet (LAN) : 00:20:0e:10:4c:aa Satellite (DVB) : 00:20:0e:10:4c:aa
    Ethernet (LAN)
# arp show
  NetAddr
                State MacAddr
   10.213.41.3 Dynamic 18:a6:f7:d3:4d:f7 1
# odu show
Pinging 10.213.41.1 with 32 bytes of data:
Reply from 10.213.41.1: bytes=32 time=558ms TTL=56
Reply from 10.213.41.1: bytes=32 time=589ms TTL=56
Reply from 10.213.41.1: bytes=32 time=569ms TTL=56
Reply from 10.213.41.1: bytes=32 time=616ms TTL=56
Reply from 10.213.41.1: bytes=32 time=560ms TTL=56
Reply from 10.213.41.1: bytes=32 time=548ms TTL=56
Reply from 10.213.41.1: bytes=32 time=582ms TTL=56
Reply from 10.213.41.1: bytes=32 time=572ms TTL=56
Reply from 10.213.41.1: bytes=32 time=569ms TTL=56
Reply from 10.213.41.1: bytes=32 time=550ms TTL=56
```

```
Ping statistics for 10.213.41.1:

Packets: Sent = 10, Received = 10, Lost = 0 (0% loss),

Approximate round trip times in milli-seconds:

Minimum = 548ms, Maximum = 616ms, Average = 571ms
```

Lista de sites acessados:

www.globo.com - ok www.hotmail.com - ok www.google.com - ok www.educacao.mg.gov.br - ok www.prodemge.mg.gov.br - ok

Responsável pelo teste de navegação:

Nome: Ronan Nunes Pereira Telefone: 38 99813-5888

Função: Diretor Masp: 1200509-6

Funcionamento: 07:00 às 17:00h