

TERMO DE ACEITE TÉCNICO


Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Rogerio Momi Frias Cliente: VIVO

> **Empresa** VSAT-ID **EMC** Brasil VIVO-PER-23093595-CE

Link kbps 256/128

Plataforma VSAT



Satellite (DVB) RX Configuration

Auto start : Enabled

Max Traffic MODCOD : 23 16APSK-9/10

: 15 minute RX watchdog

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName Name Enable Yes

* 0 0 9.320000 12.055825 DVB-S2 4 0 0.0 E

Satellite (DVB) Receiver Status

Rx State

DVB State : Forward link up

: 1326, GlobalIP@Telstar-14R Network

Frequency : 12.056086 GHz Symbol Rate : 9.320073 Msps

S2 ModCod

- receiving : 15 8PSK-5/6 - current max : 16 8PSK-8/9

Pilot : On Frame length : Short DVB S2 Mode : ACM DVB S2 Stream type: MPEG-TS

Roll off : 0.20 SNR : 13.3 dB Input Power : -23 dBm

Satellite (DVB) TX Configuration

Auto start : Enabled IDU Output Power : -22 dBm IDU Max Output Power: 0.0 dBm ODU Output Power : 34.6 dBm : 45.5 dBW EIRP

Default CW Frequency: 14.125750 GHz

ATM mode : VC-Mux Header Compression: None

Satellite (DVB) Transmitter Status

State : On (DVB-RCS) IDU Output Power : -22.9 dBm ODU Output Power : 35.4 dBm : 46.3 dBW : 11.0 dB EIRP Es/No Header Compression: Disabled Timing correction : -134 us (260381 us)

Frequency correction: 30 Hz

ping 8.8.8.8

64 bytes from 8.8.8.8: time=750 ms 64 bytes from 8.8.8.8: time=720 ms 64 bytes from 8.8.8.8: time=710 ms 64 bytes from 8.8.8.8: time=720 ms 64 bytes from 8.8.8.8: time=710 ms

--- ping statistics ---

5 packets transmitted, 5 received, 0.00 percent packet loss rtt min/avg/max = 710/720/750 ms