

TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Renan Borges Sousa Cliente: VIVO

 Empresa
 VSAT-ID
 Link kbps
 Plataforma

 EMC Brasil
 VIVO-PER-25076922-PB
 256k/128k
 VSAT



dvb tx show

Satellite (DVB) TX Configuration

Auto start : Enabled
IDU Output Power : -20 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : 33.2 dBm
EIRP : 46.5 dBW
Default CW Frequency: 0.000000 GHz

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

State : On (DVB-RCS)
IDU Output Power : -24.6 dBm
ODU Output Power : 32.7 dBm
EIRP : 46.0 dBW
Es/No : 14.5 dB
Header Compression : Disabled

Timing correction : -134 us (262141 us)

Frequency correction: 70 Hz

dvb rx show

Satellite (DVB) RX Configuration

```
_____
Auto start . Enable:
Max Traffic MODCOD : 23 16APSK-9/10
RX watchdog : 15 minute
                    : Enabled
Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName
                                                                             Name
Enable
* 0 0
         9.320000 12.055825 DVB-S2 102 0 0.0 E
Yes
Satellite (DVB) Receiver Status
______
Rx State
                   : On
                  : Forward link up
DVB State
             : 1326, GlobalIP@Telstar-14R
: 12.055976 GHz
: 9.320001 Msps
Network
Frequency
Symbol Rate
S2 ModCod
     - receiving : 1
                       QPSK-1/4
     - current max : 16 8PSK-8/9
                  : On
Pilot
Frame length
                  : Short
                   : ACM
DVB S2 Stream type : MPEG-TS
Roll off : 0.20
                  : 13.9 dB
SNR
Input Power
              : -18 dBm
IP DVB 10.50.1.133/32
Ping desde o MGMT- Server ao IP de trafego e para o DVB.
c:\Documents and Settings\Administrator.DVB-RCS>ping 10.50.1.133
Pinging 10.50.1.133 with 32 bytes of data:
Reply from 10.50.1.133: bytes=32 time=1902ms TTL=62
Reply from 10.50.1.133: bytes=32 time=559ms TTL=62
Reply from 10.50.1.133: bytes=32 time=697ms TTL=62
Reply from 10.50.1.133: bytes=32 time=581ms TTL=62
Ping statistics for 10.50.1.133:
   Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
   Minimum = 559ms, Maximum = 1902ms, Average = 934ms
Ping desde dentro da VSAT 8.8.8.8
# 64 bytes from 8.8.8.8: time=510 ms
64 bytes from 8.8.8.8: time=620 ms
64 bytes from 8.8.8.8: time=710 ms
64 bytes from 8.8.8.8: time=720 ms
64 bytes from 8.8.8.8: time=700 ms
--- 8.8.8.8 ping statistics ---
5 packets transmitted, 5 received, 0.00 percent packet loss
```

rtt min/avg/max = 510/530/550 ms