


TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Bruno Carvalho de Sá Cliente: VIVO

 Empresa
 VSAT-ID
 Link kbps
 Plataforma

 EMC Brasil
 VIVO-PER-31062707-MG
 256/128
 VSAT



dvb tx show

Satellite (DVB) TX Configuration

Auto start : Enabled

IDU Output Power : -23 dBm

IDU Max Output Power: 0.0 dBm

ODU Output Power : 33.7 dBm

EIRP : 47.0 dBW

Default CW Frequency: 14.125750 GHz ATM mode : VC-Mux

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status
-----State : On (DVB-RCS)
IDU Output Power : -22.5 dBm

```
ODU Output Power : 33.6 dBm
EIRP : 46.9 dBW Es/No : 13.0 dB
Header Compression : Disabled
Timing correction : -88 us (260693 us)
Frequency correction: 210 Hz
# dvb rx show
Satellite (DVB) RX Configuration
-----
Auto start : Enabled
Max Traffic MODCOD : 23 16APSK-9/10
RX watchdog : 15 minute
Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName
                                                                               Name
Enable
         9.320000 12.055825 DVB-S2 102 0 0.0 E
* 0 0
Yes
Satellite (DVB) Receiver Status
           : On
: Forward link up
Rx State
DVB State
                   : 1326, GlobalIP@Telstar-14R
Network
Frequency : 12.055938 GHz
Symbol Rate : 9.320059 Msps
S2 ModCod
  - receiving : 1 QPSK-1/4
     - current max: 16 8PSK-8/9
Pilot : On
Frame length : Short
DVB S2 Mode : ACM
DVB S2 Stream type : MPEG-TS
Roll off : 0.20
SNR
                   : 13.0 dB
Input Power
                   : -28 dBm
# ping 8.8.8.8
64 bytes from 8.8.8.8: time=810 ms
64 bytes from 8.8.8.8: time=880 ms
64 bytes from 8.8.8.8: time=950 ms
64 bytes from 8.8.8.8: time=1030 ms
64 bytes from 8.8.8.8: time=1110 ms
--- ping statistics ---
5 packets transmitted, 5 received, 0.00 percent packet loss
rtt min/avg/max = 810/950/1110 ms
```



