

TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Leonardo Martins

Cliente: VIVO

Empresa
EMC Brasil

VSAT-ID
VIVO-PER-27006972-AL

Link kbps
256k/128k

Plataforma
VSAT



Termin 10.29.56.73

Satellite (DVB) TX Configuration

Auto start : Enabled
 IDU Output Power : -20 dBm
 IDU Max Output Power : 0.0 dBm
 ODU Output Power : max
 EIRP : max
 Default CV Frequency : 0.000000 GHz
 RF mode : UC-Pass
 Header Compression : None

Satellite (DVB) Transmitter Status

State : On (DVB-MCS2)
 IDU Output Power : -11.6 dBm
 ODU Output Power : 33.4 dBm
 EIRP : 46.7 dBm
 Eo/No : 12.5 dB
 Header Compression : Disabled
 Timing correction : -58 us (250661 us)
 Frequency correction : -60 Hz

Satellite (DVB) RX Configuration

Auto start : Enabled
 Max Traffic MODCOD : 23 16APSK-9/10
 RX watching : 15 minute

| Idx | Freq | SymbRate(Mega) | Freq(GHz) | Mode | PopId | SatId | Pos | SatName |
|-----|------|----------------|-----------|------------|-------|-------|-----|---------|
| 0 | 0 | 25.333333 | 12.050000 | DVB-S2 102 | 0 | 0.0 | E | |
| 1 | 1 | 15.000000 | 12.050000 | DVB-S2 4 | 0 | 0.0 | E | |

Satellite (DVB) Receiver Status

Rx State : On
 DVB State : Forward link up
 Network : 1326 1148 Beam
 Frequency : 12.050225 GHz
 Symbol Rate : 25.333137 Mega
 S2 ModCod : 20 16APSK-4/5
 - current max : 20 16APSK-4/5
 Pilot : On
 Frame length : Short
 DVB S2 Mode : ACR
 DVB S2 Stream type : MF50-TS
 Roll off : 0.20
 SNR : 13.6 dB
 Input Power : -25 dBm

SatLink VSAT

10.29.56.73/wmi/dwp/index_page.dwp

Status

Satellite Statistics

Device

DHCP

Eventlog

Configuration

Satellite

IP

Static NAT

Lineup

Device

Help

Introduction

Status

Configuration

Device Status

| Model | Software Version | LAN MAC Address | DVB MAC Address | System Up Time | CPU Load | System Name | System Contact | System Location | ODU Serial Number | ODU HW Version |
|--------------|------------------|-------------------|-------------------|------------------|----------|----------------------|----------------|---------------------------|--------------------------|----------------|
| SatLink 2000 | 16.0 1.57 | 00:20:0e:10:55:43 | 00:20:0e:10:55:43 | 0 days, 00:03:15 | 19% | VIVO-PER-27006972-AL | | Poço das Trincheiras - AL | 104804040203090604410000 | 4.2 |

You are logged in as install (2)

© Copyright 2006-2014 STM Group. All Rights Reserved.

SatLink VSAT

SpeedOfLife: HTML5 Sp... X

10.29.56.73/wmi/dwp/index_page.dwp

Status

Satellite Statistics

Device

DHCP

Eventlog

Configuration

Satellite

IP

Static NAT

Lineup

Device

Help

Introduction

Status

Configuration

Device Status

| Model | Software Version | LAN MAC Address | DVB MAC Address | System Up Time | CPU Load | System Name | System Contact | System Location | ODU Serial Number | ODU HW Version |
|--------------|------------------|-------------------|-------------------|------------------|----------|----------------------|----------------|---------------------------|--------------------------|----------------|
| SatLink 2000 | 16.0 1.57 | 00:20:0e:10:55:43 | 00:20:0e:10:55:43 | 0 days, 00:03:15 | 19% | VIVO-PER-27006972-AL | | Poço das Trincheiras - AL | 104804040203090604410000 | 4.2 |

You are logged in as install (2)

© Copyright 2006-2014 STM Group. All Rights Reserved.

C:\Windows\system32\cmd.exe

```

Resposta de 8.8.8.8: bytes=32 tempo=1768ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=577ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=543ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=852ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=570ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=544ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=765ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=670ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=861ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1362ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=574ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=765ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=842ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=551ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=641ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1411ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=720ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1305ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=895ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=761ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1145ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1741ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=793ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1210ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1451ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1389ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=711ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=862ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=806ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=2434ms TTL=44
Esgotado o tempo limite de pedido.
Resposta de 8.8.8.8: bytes=32 tempo=1226ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=2519ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=715ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1861ms TTL=44

Estatísticas de Ping para 8.8.8.8:
Pacotes: Enviados = 76, Recebidos = 75, Perdidos = 1 (1% de perda).
Aproximar um número redondo de vezes em milissegundos:
Mínimo = 551ms, Máximo = 2804ms, Média = 1181ms.

Control-C
C:\Users\DJTernados>arp -a

Interface: 10.29.56.74 --- Bch
Endereço IP      Endereço físico  Tipo
10.29.56.73      00-20-0e-10-55-43  dinâmico
10.29.56.79      ff-ff-ff-ff-ff-ff  estático
224.0.0.2        01-00-5e-00-00-02  estático
224.0.0.251      01-00-5e-00-00-1b  estático
224.0.0.252      01-00-5e-00-00-1c  estático
224.0.1.68       01-00-5e-00-00-1c  estático
239.255.255.250  01-00-5e-7f-ff-fa  estático
255.255.255.255  ff-ff-ff-ff-ff-ff  estático

```