

TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

Cliente: VIVO NOC/Operador: Rogério Momi Frias

> **Empresa** VSAT-ID Link kbps Plataforma **EMC** Brasil 256/128 **VSAT** VIVO-PER-23094788-CE



Satellite (DVB) RX Configuration

Auto start : Enabled

Max Traffic MODCOD : 23 16APSK-9/10

: 15 minute RX watchdog

ldx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName Name Enable * 0 0 9.320000 12.055825 DVB-S2 4 0 0.0 E Yes

Satellite (DVB) Receiver Status

Rx State : On

DVB State : Forward link up

: 1326, GlobalIP@Telstar-14R Network

: 12.055947 GHz Frequency Symbol Rate : 9.320280 Msps

S2 ModCod

- receiving : 15 8PSK-5/6 - current max : 16 8PSK-8/9

Pilot : On Frame length : Short DVB S2 Mode : ACM

DVB S2 Stream type: MPEG-TS

Roll off : 0.20 SNR : 13.5 dB Input Power : -27 dBm

Satellite (DVB) TX Configuration

Auto start : Enabled IDU Output Power : -22 dBm IDU Max Output Power: 0.0 dBm ODU Output Power : 35.6 dBm

EIRP : 45.5 dBW

Default CW Frequency: 14.125750 GHz

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

State : On (DVB-RCS)
IDU Output Power : -22.1 dBm
ODU Output Power : 35.8 dBm

EIRP : 45.7 dBW Es/No : 12.0 dB

Header Compression: Disabled

Timing correction : -102 us (260452 us)

Frequency correction: -110 Hz

ping 8.8.8.8

64 bytes from 8.8.8.8: time=710 ms 64 bytes from 8.8.8.8: time=710 ms 64 bytes from 8.8.8.8: time=620 ms 64 bytes from 8.8.8.8: time=830 ms 64 bytes from 8.8.8.8: time=700 ms

--- ping statistics ---

5 packets transmitted, 5 received, 0.00 percent packet loss rtt min/avg/max = 620/710/830 ms