

EMC Brasil

TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Wallace Teixeira

Cliente: VIVO

Empresa

VSAT-ID VIVO-PERLink kbps 256k/128k

Plataforma VSAT

27028356-AL



dvb tx show

Satellite (DVB) TX Configuration

Auto start : Enabled
IDU Output Power : -20 dBm
IDU Max Output Power: 0.0 dBm
Default CW Frequency: 0.000000 GHz

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

State : On (DVB-RCS2)
IDU Output Power : -20.0 dBm

Es/No : 11.5 dB

Header Compression: Disabled

Timing correction: -19 us (250305 us)

Frequency correction: -90 Hz

dvb rx show

Satellite (DVB) RX Configuration

Auto start : Enabled

Max Traffic MODCOD : 23 16APSK-9/10

RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName Name Enable

* 0 0 30.000000 11.592000 DVB-S2 102 0 0.0 E Yes 1 1 25.333000 11.592000 DVB-S2 4 0 0.0 E Yes

Satellite (DVB) Receiver Status

Rx State : On

DVB State : Forward link up

Network : 1326, T14R Beam

Frequency : 11.591962 GHz

Symbol Rate : 30.000303 Msps

S2 ModCod

- receiving : 14 8PSK-3/4

- current max : 21 16APSK-5/6

Pilot : On

Frame length : Short DVB S2 Mode : ACM

DVB S2 Stream type: MPEG-TS

Roll off : 0.20 SNR : 14.8 dB

Input Power : -32 dBm

