


## TERMO DE ACEITE TÉCNICO

Solicitante: PRODEMGE / SEE

NOC/Operadora: Wallace Teixeira Operadora/Cliente: Gilvan P de Brito Júnior

GRE/Prodemge: João Antinossi Responsável/cliente: Ronan Nunes Pereira

> Consórcio **VSAT-ID** Porta kbps **Plataforma** EMC/Vodanet 2MBPS SEE-SAES-22241 **VSAT**



# dvb rx show

Satellite (DVB) RX Configuration \_\_\_\_\_

Auto start : Enables

Max Traffic MODCOD : 23 16APSK-9/10

RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName Name

Enable

4.883300 12.176420 DVB-S2 104 0 0.0 E \* 0 0

Yes

Satellite (DVB) Receiver Status

Rx State : On

DVB State : Forward link up

Network : 65281, Prodemge@Vodanet

Frequency : 12.176365 GHz

Symbol Rate : 4.883000 Msps

S2 ModCod

S2 ModCod

- receiving : 4 QPSK-1/2 - current max : 21 16APSK-5/6

Pilot : On
Frame length : Short
DVB S2 Mode : ACM
DVB S2 Stroom DVB S2 Stream type : MPEG-TS

```
Roll off
                    : 0.20
SNR
                    : 15.6 dB
Input Power
                    : -30 dBm
# dvb tx show
Satellite (DVB) TX Configuration
-----
Auto start
                    : Enabled
Auto start : Enabled IDU Output Power : -30 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : 33.2 dBm
EIRP
                    : 46.5 dBW
Default CW Frequency: 0.000000 GHz
ATM mode : VC-Mux
Header Compression : UDP/IP
Satellite (DVB) Transmitter Status
_____
State : On (DVB-RCS2)
IDU Output Power : -20.6 dBm
ODU Output Power : 33.3 dBm
EIRP
                    : 46.6 dBW
Es/No
                     : 12.5 dB
\hbox{{\tt Header Compression}} \quad \hbox{{\tt :}} \quad \hbox{{\tt Disabled}} \quad \hbox{{\tt - HC for RCS2 not supported by HUB}}
Timing correction : -192 us (281180 us)
Frequency correction: 50 Hz
# device show
System Information:
            : SEE-SAES-22241
   Name
    Location
                        : SÃO JOÃO DAS MISSÕES - MG
    Contact
    System Up time : 0 days, 00:20:54
CPU Load : 17%
System time(UTC) : 29 October 2017 23:07:39
    Broadcast Message : not set
HW:
    Model
                        : SatLink 2000
    HW ID
                        : 120033
    Main board ID
                        : 120026 R6.2
MAC addresses:
   Ethernet (LAN) : 00:20:0e:10:5b:4b
Satellite (DVB) : 00:20:0e:10:5b:4b
# arp show
             State MacAddr
                                             Ιf
    10.213.40.2 Dynamic e8:9a:8f:b7:bd:4a 1
Pinging 10.213.40.1 with 32 bytes of data:
Reply from 10.213.40.1: bytes=32 time=586ms TTL=56
Reply from 10.213.40.1: bytes=32 time=566ms TTL=56
Reply from 10.213.40.1: bytes=32 time=599ms TTL=56
Reply from 10.213.40.1: bytes=32 time=591ms TTL=56
Reply from 10.213.40.1: bytes=32 time=578ms TTL=56
Reply from 10.213.40.1: bytes=32 time=549ms TTL=56
Reply from 10.213.40.1: bytes=32 time=557ms TTL=56
Reply from 10.213.40.1: bytes=32 time=545ms TTL=56
Reply from 10.213.40.1: bytes=32 time=581ms TTL=56
Ping statistics for 10.213.40.1:
    Packets: Sent = 9, Received = 9, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
```

Minimum = 545ms, Maximum = 599ms, Average = 572ms
Lista de sites acessados:  www.globo.com - ok  www.yahoo.com - ok  www.hotmail.com - ok  www.google.com - ok  www.google.com - ok  www.educacao.mg.gov.br - ok  www.prodemge.gov.br - ok
Responsável pelo teste de navegação: Nome: Ronan Nunes Pereira Função: Diretor Identidade: Masp- 1200509-6