

TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Guilherme Cunha Cliente: VIVO

 Empresa
 VSAT-ID
 Link kbps
 Plataforma

 EMC Brasil
 VIVO-PER-23177128-CE
 256k/128k
 VSAT



dvb tx show

Satellite (DVB) TX Configuration

Auto start : Enabled
IDU Output Power : -20 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : 33.5 dBm
EIRP : 46.5 dBW
Default CW Frequency: 0.000000 GHz

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

State : On (DVB-RCS2)

IDU Output Power : -14.9 dBm

ODU Output Power : 33.4 dBm

EIRP : 46.4 dBW

Es/No : 13.5 dB

Header Compression : Disabled

Timing correction : -50 us (249475 us)

Frequency correction: -110 Hz

dvb rx show

Satellite (DVB) RX Configuration

______ Auto start : Enabled
Max Traffic MODCOD : 23 16APSK-9/10
RX watchdog : 15 minute

Idx	Pri	SymbRate[Msps]	Freq[GHz]	Mode	PopId	SatId	Pos	SatName	Name
Enable									
0	0	15.000000	12.059000	DVB-S2	102	0	0.0 E		
Yes									
1	1	9.320000	12.055825	DVB-S2	4	0	0.0 E		
Yes									
* 6	6	25.333333	12.050000	DVB-S2	102	0	0.0 E		
Yes									
7	7	30.000000	12.050000	DVB-S2	102	0	0.0 E		
Yes									

Satellite (DVB) Receiver Status

Rx State : On

DVB State : Forward link up

Network : 1326, T14R Beam

Frequency : 12.049836 GHz

Symbol Rate : 25.333237 Msps

S2 ModCod

- receiving : 14 8PSK-3/4 - current max : 22 16APSK-8/9

Pilot : On
Frame length : Short
DVB S2 Mode : ACM DVB S2 Stream type : MPEG-TS Roll off : 0.20 SNR : 14.7 dB Input Power : -23 dBm

```
isticat do Ping para 8.8.8.8:
acotes: Enviados - 160. Recebidos - 150. Perdidos - 2 (1x de
perda).
         um número redondo de vezes em miliosegundos:
- 555ms, Móximo - 3344ms, Média - 1222ms
```