

## TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais Cliente: VIVO NOC/Operador: Guilherme Henrique **Empresa** VSAT-ID Link kbps Plataforma **EMC** Brasil VIVO-PER-27025578-AL 256k/128k **VSAT** 



# dvb rx show

Satellite (DVB) RX Configuration : Enabled Auto start

Max Traffic MODCOD : 23 16APSK-9/10 RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName Name

Enable

\* 0 0 30.000000 12.050000 DVB-S2 102 0 0.0 E

Yes

1 1 12.050000 DVB-S2 4 0 0.0 E 25.333333

Yes

Satellite (DVB) Receiver Status \_\_\_\_\_

Rx State : On

: Forward link up : 1326, T14R Beam DVB State Network Frequency : 12.050069 GHz : 30.000427 Msps Symbol Rate

## S2 ModCod - receiving : 19 16APSK-3/4 - current max : 22 16APSK-8/9 : On Pilot Frame length : Short DVB S2 Mode : ACM DVB S2 Stream type : MPEG-TS : 0.20 Roll off : 15.7 dB SNR : -33 dBm Input Power # dvb tx show Satellite (DVB) TX Configuration \_\_\_\_\_\_ Auto start : Enabled IDU Output Power : -20 dBm IDU Max Output Power: 0.0 dBm Default CW Frequency: 0.000000 GHz ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

: On (DVB-RCS2)

IDU Output Power : -19.8 dBm

Es/No Header Compression : Disabled

Timing correction : -96 us (250078 us)

Frequency correction: -50 Hz

