

TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Wallace Teixeira

Cliente: Vivo

Empresa
EMC Brasil
VIVO-PER-25101293-PB
Link kbps
256K/128K
VSAT



dvb tx show

Satellite (DVB) TX Configuration

Auto start : Enabled IDU Output Power : -20 dBm IDU Max Output Power: 0.0 dBm

Default CW Frequency: 0.000000 GHz

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

State : On (DVB-RCS2)

IDU Output Power : -20.1 dBm Es/No : 11.5 dB Header Compression : Disabled

Timing correction : -47 us (251451 us)

Frequency correction: -50 Hz

dvb rx show

Satellite (DVB) RX Configuration

Auto start : Enabled
Max Traffic MODCOD : 23 16APSK-9/10
RX watchdog : 15 minute

Idx	Pri	SymbRate[Msps]	Freq[GHz]	Mode	PopId	SatId	Pos	SatName
Name		Enable						
* 0	0	25.333333	12.050000	DVB-S2	102	0	0.0 E	
Yes								
7	7	30.000000	12.050000	DVB-S2	102	0	0.0 E	

Yes

Satellite (DVB) Receiver Status

Rx State : On

DVB State : Forward link up

Network : 1326, T14R Beam

Frequency : 12.050056 GHz

Symbol Rate : 25.333237 Msps

S2 ModCod

- receiving : 18 16APSK-2/3 - current max : 22 16APSK-8/9

Pilot : On
Frame length : Short
DVB S2 Mode : ACM DVB S2 Stream type : MPEG-TS Roll off : 0.20 SNR : 15.7 SNR : 15.7 dB Input Power : -35 dBm

