


## TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Alexandre Cruz Cliente: VIVO

 Empresa
 VSAT-ID
 Link kbps
 Plataforma

 EMC Brasil
 VIVO-PER-23006579-CE
 256/128
 VSAT



# dvb rx show

Satellite (DVB) RX Configuration
----Auto start : Enabled

Max MODCOD : 23 16APSK-9/10 (SNR threshold: 23.5 dB)

RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId Enable
\* 0 0 9.320000 12.055825 DVB-S2 4 Yes

Satellite (DVB) Receiver Status

Rx State : On

DVB State : Forward link up

Network : 1326, GlobalIP@Telstar-14R

```
Frequency : 12.055625 GHz
Symbol Rate : 9.319934 Msps
S2 ModCod
 - receiving : 1 QPSK-1/4
- current max : 23 16APSK-9/10
Pilot : On
Frame length : Short
DVB S2 Mode : ACM
DVB S2 Mode
                     : 0.25
Roll off
                 : 16.1 dB
: -25 dBm
SNR
Input Power
# dvb tx show
Satellite (DVB) TX Configuration
_____
Auto start : Enabled IDU Output Power : -15 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : 34.2 dBm EIRP : 47.5 dBW
Default CW Frequency: 0.000000 GHz
ATM mode : VC-Mux
Header Compression : None
Satellite (DVB) Transmitter Status
State : On (TDMA)

IDU Output Power : -19.2 dBm

ODU Output Power : 34.0 dBm
EIRP : 47.3 dBW Eb/No : 15.0 dB
                    : 47.3 dBW
Header Compression : Disabled
Timing correction : -251 us (260490 us)
Frequency correction: -100 Hz
IP DVB 10.53.0.249/32
Ping desde o MGMT- Server ao IP de trafego e para o DVB.
Ping desde dentro da VSAT 8.8.8.8
# ping 8.8.8.8
64 bytes from 8.8.8.8: time=2740 ms
64 bytes from 8.8.8.8: time=910 ms
64 bytes from 8.8.8.8: time=930 ms
64 bytes from 8.8.8.8: time=940 ms
64 bytes from 8.8.8.8: time=910 ms
--- 8.8.8.8 ping statistics ---
5 packets transmitted, 5 received, 0.00 percent packet loss
rtt min/avg/max = 910/1280/2740 ms
```