


## **TERMO DE ACEITE TÉCNICO**

Solicitante: SES - Secretaria de Estado de Saúde de Minas Gerais Data: 28/12/2011

NOC/Operadora: Olivan Neves Operadora/Cliente: Deferson de Oliveira

**GRE/Prodemge:** Douglas Alvares Responsável/cliente: Lilian Castro

Consórcio Porta kbps VSAT-ID **Plataforma** STM/Vodanet 384/153 SES-ANAS-0657 **VSAT** 



## Satellite (DVB) RX Configuration

Auto start : Enabled

: 15 8PSK-5/6 (SNR threshold: 9.6 dB) Max MODCOD

ACM Latency : On RX watchdoq : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId Enable \* 0 0 7.120000 11.583700 DVB-S2 2

## Satellite (DVB) Receiver Status

Rx State : On

DVB State : Forward link up

: 65281, Prodemge@Vodanet Network

: 11.583920 GHz : 7.120007 Msps Frequency Symbol Rate

S2 ModCod

- receiving : 13 8PSK-2/3 - current max : 22 16APSK-8/9

Pilot : On

Frame length : Short frame

DVB S2 Mode : ACM Roll off : 0.25 : 14.6 dB SNR Input Power : -29 dBm

```
Satellite (DVB) TX Configuration
_____
Auto start
                   : Enabled
Auto start

IDU output power : -15 dBm

EIRP : 47.5 dBW
Default CW Frequency: 0.000000 GHz
ATM mode : VC-Mux
Header Compression : UDP/IP/DSM-CC
Satellite (DVB) Transmitter Status
______
State : On (TDMA)

IDU Output Power : -15.1 dBm

ODU Output Power : 34.2 dBm
EIRP
                    : 47.5 dBW
Eb/No
                    : 14.0 dB
Header Compression : DSM-CC
Timing correction : -275 us (271070 us)
Frequency correction: -350 Hz
Pinging 10.144.13.1 with 32 bytes of data:
Reply from 10.144.13.1: bytes=32 time=599ms TTL=61
Reply from 10.144.13.1: bytes=32 time=707ms TTL=61
Reply from 10.144.13.1: bytes=32 time=625ms TTL=61
Reply from 10.144.13.1: bytes=32 time=553ms TTL=61
Reply from 10.144.13.1: bytes=32 time=661ms TTL=61
Reply from 10.144.13.1: bytes=32 time=580ms TTL=61
Reply from 10.144.13.1: bytes=32 time=692ms TTL=61
Reply from 10.144.13.1: bytes=32 time=615ms TTL=61
Reply from 10.144.13.1: bytes=32 time=538ms TTL=61
Reply from 10.144.13.1: bytes=32 time=641ms TTL=61
Ping statistics for 10.144.13.1:
   Packets: Sent = 10, Received = 10, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
   Minimum = 538ms, Maximum = 707ms, Average = 621ms
```