

# **TERMO DE ACEITE TÉCNICO**


Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Rogerio Momi Frias Cliente: VIVO

> Empresa VSAT-ID

**EMC** Brasil VIVO-PER-31250279-MG Link kbps 256/128

**Plataforma VSAT** 



#### Satellite (DVB) RX Configuration

: Enabled Auto start

Max MODCOD : 23 16APSK-9/10 (SNR threshold: 23.5 dB)

RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId Enable \* 0 0 9.320000 12.055825 DVB-S2 4 Yes

## Satellite (DVB) Receiver Status

-----

Rx State : On **DVB State** 

: Forward link up

: 1326, GlobalIP@Telstar-14R Network

Frequency : 12.055919 GHz Symbol Rate : 9.319802 Msps

S2 ModCod

- receiving : 1 QPSK-1/4 - current max : 23 16APSK-9/10

Pilot : On

Frame length : Short DVB S2 Mode : ACM Roll off : 0.25 SNR : 14.7 dB : -26 dBm Input Power

#### Satellite (DVB) TX Configuration

-----

Auto start : Enabled IDU Output Power : -30 dBm IDU Max Output Power: 0.0 dBm ODU Output Power : 34.7 dBm : 48.0 dBW EIRP

Default CW Frequency: 0.000000 GHz

ATM mode : VC-Mux Header Compression: None

### Satellite (DVB) Transmitter Status

-----

State : On (TDMA) IDU Output Power : -18.6 dBm ODU Output Power : 34.6 dBm : 47.9 dBW : 14.5 dB EIRP Es/No Header Compression: Disabled

Timing correction: 30 us (262314 us)

Frequency correction: -330 Hz

# ping 8.8.8.8

64 bytes from 8.8.8.8: time=680 ms 64 bytes from 8.8.8.8: time=570 ms 64 bytes from 8.8.8.8: time=580 ms 64 bytes from 8.8.8.8: time=630 ms 64 bytes from 8.8.8.8: time=1020 ms

## --- 8.8.8.8 ping statistics ---

5 packets transmitted, 5 received, 0.00 percent packet loss rtt min/avg/max = 570/690/1020 ms