


TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

Cliente: VIVO NOC/Operador: Rogerio Momi Frias

> **Empresa** VSAT-ID Link kbps **EMC** Brasil VIVO-PER-26078694-PE

Plataforma 256/128 **VSAT**



Satellite (DVB) RX Configuration

Auto start : Enabled

Max Traffic MODCOD : 23 16APSK-9/10

RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName Name Enable * 0 0 9.320000 12.055825 DVB-S2 102 0 0.0 E Yes

Satellite (DVB) Receiver Status

Rx State : On

DVB State

: Forward link up

: 1326, GloballP@Telstar-14R Network

Frequency : 12.056012 GHz : 9.320008 Msps Symbol Rate

S2 ModCod

- receiving : 1 QPSK-1/4 - current max : 16 8PSK-8/9

Pilot : On Frame length : Short

DVB S2 Mode : ACM

DVB S2 Stream type: MPEG-TS

Roll off : 0.20 SNR : 13.6 dB Input Power : -25 dBm

Satellite (DVB) TX Configuration

Auto start : Enabled IDU Output Power : -19 dBm IDU Max Output Power: 0.0 dBm ODU Output Power : 35.0 dBm

EIRP : 48.0 dBW

Default CW Frequency: 14.125750 GHz

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

State : On (DVB-RCS) IDU Output Power : -18.6 dBm ODU Output Power : 34.5 dBm

EIRP : 47.5 dBW Es/No : 14.0 dB

Header Compression: Disabled

Timing correction : -182 us (262195 us)

Frequency correction: -20 Hz

ping 8.8.8.8

64 bytes from 8.8.8.8: time=1160 ms 64 bytes from 8.8.8.8: time=610 ms 64 bytes from 8.8.8.8: time=640 ms 64 bytes from 8.8.8.8: time=630 ms 64 bytes from 8.8.8.8: time=590 ms

--- ping statistics ---

5 packets transmitted, 5 received, 0.00 percent packet loss rtt min/avg/max = 590/720/1160 ms