

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Guilherme Cunha


Cliente: VIVO

Empresa
EMC Brasil

VSAT-ID
VIVO-PER-27004015-SE

Link kbps
256k/128k

Plataforma
VSAT



Satellite (DVB) TX Configuration

```
Auto start           : Enabled
IDU Output Power     : -20 dBm
IDU Max Output Power : 0.0 dBm
ODU Output Power     : max
EIRP                 : max
Default CW Frequency : 0.000000 GHz
ATM mode              : VC-Mux
Header Compression   : None
```

Satellite (DVB) Transmitter Status

```
State                : On (DVB-RCS2)
IDU Output Power     : -8.6 dBm
ODU Output Power     : 33.0 dBm
EIRP                 : 46.3 dBW
Es/No                : 12.5 dB
Header Compression   : Disabled
Timing correction     : -31 us (250587 us)
Frequency correction : -60 Hz
```

Satellite (DVB) RX Configuration

```
Auto start           : Enabled
Max Traffic MODCOD    : 23 16APSK-9/10
RX watchdog           : 15 minute
```

Idx	Pri	SymbRate[Mbps]	Freq[GHz]	Mode	PopId	SatId	Pos	SatName	Name
Enable									
* 0	0	25.333333	12.050000	DVB-S2	102	0	0.0 E		
Yes									
1	1	15.000000	12.059000	DVB-S2	4	0	0.0 E		
Yes									

Satellite (DVB) Receiver Status

```

-----
Rx State           : On
DVB State          : Forward link up
Network            : 1326,  T14R Beam
Frequency          : 12.049947 GHz
Symbol Rate        : 25.333070 Msps
S2 ModCod
- receiving        : 20    16APSK-4/5
- current max      : 22    16APSK-8/9
Pilot              : On
Frame length       : Short
DVB S2 Mode        : ACM
DVB S2 Stream type : MPEG-TS
Roll off           : 0.20
SNR                : 14.7 dB
Input Power        : -28 dBm

```

C:\Windows\system32\cmd.exe

```

Resposta de 8.8.8.8: bytes=32 tempo=861ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=686ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=670ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=707ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=702ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=624ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=895ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=879ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=500ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=670ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=695ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=675ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=750ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=830ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=555ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=904ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1657ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=855ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=926ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=602ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=646ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=748ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=791ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=840ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=573ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=637ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=646ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=734ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=816ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=870ms TTL=44

Estatísticas do Ping para 8.8.8.8:
Pacotes: Enviados = 46, Recebidos = 46, Perdidos = 0 (0% de
perda).
Aproximar um número redondo de vezes em milissegundos:
Mínimo = 555ms, Máximo = 1669ms, Média = 773ms
Control-C
^C
C:\Users\DjTornados>arp-r
'arp-r' não é reconhecido como um comando interno
ou externo, um programa operável ou um arquivo em lotes.
C:\Users\DjTornados>arp -a

Interface: 10.29.56.2 --- 0xb
Endereço IP      Endereço físico      Tipo
10.29.56.1       00-20-0e-10-4a-d0    dinâmico
10.29.56.7       ff-ff-ff-ff-ff-ff    estático
224.0.0.2        01-00-5e-00-00-02    estático
224.0.0.251      01-00-5e-00-00-fb    estático
224.0.0.252      01-00-5e-00-00-fc    estático
224.0.1.60       01-00-5e-00-01-3c    estático
239.255.255.250  01-00-5e-7f-ff-fa    estático
255.255.255.255  ff-ff-ff-ff-ff-ff    estático

```

SatLink VSAT

10.29.56.1/wmi/dwp/index_page.dwp

Status

Satellite

Statistics

Device

DHCP

Eventlog

Configuration

Satellite

Static NAT

Lineup

Device

Help

Introduction

Status

Configuration

Device Status

Model	SatLink 2000
Software Version	16.0.1.57
LAN MAC Address	00:20:0e:10:4a:d0
DVB MAC Address	00:20:0e:10:4a:d0
System Up Time	0 days, 00:05:58
CPU Load	18%
System Name	VIVO-PER-27004015-SE
System Contact	
System Location	PIRANHAS - SE
ODU Serial Number	104804040203090208420000
ODU HW Version	4.2

You are logged in as install (2)

© Copyright 2006-2014 STM Group. All Rights Reserved.