

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Rogério Momi Frias


Cliente: VIVO

Empresa
EMC Brasil

VSAT-ID
VIVO-PER-31168955-MG

Link kbps
256/128

Plataforma
VSAT



Satellite (DVB) RX Configuration

Auto start : Enabled
Max MODCOD : 23 16APSK-9/10 (SNR threshold: 23.5 dB)
RX watchdog : 15 minute

Idx	Pri	SymbRate[Mbps]	Freq[GHz]	Mode	PopId	Enable
* 0	0	9.320000	12.055825	DVB-S2 4		Yes

Satellite (DVB) Receiver Status

Rx State : On
DVB State : Forward link up
Network : 1326, GlobalIP@Telstar-14R
Frequency : 12.055621 GHz
Symbol Rate : 9.319794 Msps
S2 ModCod
- receiving : 14 8PSK-3/4
- current max : 23 16APSK-9/10
Pilot : On
Frame length : Short
DVB S2 Mode : ACM
Roll off : 0.25
SNR : 13.5 dB
Input Power : -29 dBm

Satellite (DVB) TX Configuration

Auto start : Enabled
IDU Output Power : -20 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : 35.2 dBm
EIRP : 48.5 dBW
Default CW Frequency: 14.169600 GHz
ATM mode : VC-Mux
Header Compression : None

Satellite (DVB) Transmitter Status

State : On (TDMA)
IDU Output Power : -17.4 dBm
ODU Output Power : 34.9 dBm
EIRP : 48.4 dBW
Eb/No : 13.0 dB
Header Compression : Disabled
Timing correction : -236 us (260455 us)
Frequency correction: -230 Hz

ping 8.8.8.8

64 bytes from 8.8.8.8: time=1820 ms
64 bytes from 8.8.8.8: time=1200 ms
64 bytes from 8.8.8.8: time=1870 ms
64 bytes from 8.8.8.8: time=1370 ms
64 bytes from 8.8.8.8: time=1790 ms

--- 8.8.8.8 ping statistics ---

5 packets transmitted, 5 received, 0.00 percent packet loss
rtt min/avg/max = 1200/1610/1870 ms