

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Allan Santos

Cliente: VIVO

Empresa
EMC Brasil

VSAT-ID
VIVO-PER-25059840-PB

Link kbps
256k/128k

Plataforma
VSAT



SatLink


- Status
- Satellite
- Statistics
- Device
- DHCP
- Eventlog
- Configuration
- Satellite
- IP
- Static NAT
- Lineup
- Device
- Tools
- Help
- Introduction
- Status
- Configuration

```
Telnet 10.29.31.217
Es/No : 9.5 dB
Header Compression : Disabled
Timing correction : -29 us (262163 us)
Frequency correction: 160 Hz
#
Satellite <DVB> TX Configuration
-----
Auto start : Enabled
BUPC status : Disabled
IDU Output Power : -20 dBm
IDU Max Output Power: 0.0 dBm
Default CW Frequency: 0.000000 GHz
ATM mode : UC-Mux
Header Compression : None
#
Satellite <DVB> Transmitter Status
-----
State : On <DVB-RCS>
IDU Output Power : -19.9 dBm
Es/No : 14.0 dB
Header Compression : Disabled
Timing correction : -29 us (262163 us)
Frequency correction: 160 Hz
#
```

Receive Signal

☐ Audio

Rx SNR [dB]



You are logged in as root (1)

© Copyright 2006-2016 EMC SatCom Technologies Norway AS ®. All Rights Reserved.

Administrador: Prompt de Comando

```
Resposta de 8.8.8.8: bytes=32 tempo=634ms TTL=42
Resposta de 8.8.8.8: bytes=32 tempo=1531ms TTL=42
Resposta de 8.8.8.8: bytes=32 tempo=711ms TTL=42
Resposta de 8.8.8.8: bytes=32 tempo=635ms TTL=42
Resposta de 8.8.8.8: bytes=32 tempo=1734ms TTL=42
Resposta de 8.8.8.8: bytes=32 tempo=591ms TTL=42
Resposta de 8.8.8.8: bytes=32 tempo=1450ms TTL=42
Resposta de 8.8.8.8: bytes=32 tempo=611ms TTL=42
Resposta de 8.8.8.8: bytes=32 tempo=1863ms TTL=42
Resposta de 8.8.8.8: bytes=32 tempo=1202ms TTL=42
Resposta de 8.8.8.8: bytes=32 tempo=1021ms TTL=42
Resposta de 8.8.8.8: bytes=32 tempo=635ms TTL=42
Resposta de 8.8.8.8: bytes=32 tempo=1958ms TTL=42
Resposta de 8.8.8.8: bytes=32 tempo=631ms TTL=42
Resposta de 8.8.8.8: bytes=32 tempo=1381ms TTL=42
Resposta de 8.8.8.8: bytes=32 tempo=749ms TTL=42
Resposta de 8.8.8.8: bytes=32 tempo=672ms TTL=42
Resposta de 8.8.8.8: bytes=32 tempo=936ms TTL=42
Resposta de 8.8.8.8: bytes=32 tempo=1323ms TTL=42
Resposta de 8.8.8.8: bytes=32 tempo=1512ms TTL=42
Resposta de 8.8.8.8: bytes=32 tempo=923ms TTL=42
Resposta de 8.8.8.8: bytes=32 tempo=964ms TTL=42
Resposta de 8.8.8.8: bytes=32 tempo=696ms TTL=42
Resposta de 8.8.8.8: bytes=32 tempo=1767ms TTL=42
Resposta de 8.8.8.8: bytes=32 tempo=566ms TTL=42
Resposta de 8.8.8.8: bytes=32 tempo=946ms TTL=42
Resposta de 8.8.8.8: bytes=32 tempo=566ms TTL=42
Resposta de 8.8.8.8: bytes=32 tempo=578ms TTL=42
Resposta de 8.8.8.8: bytes=32 tempo=626ms TTL=42
Resposta de 8.8.8.8: bytes=32 tempo=748ms TTL=42
Resposta de 8.8.8.8: bytes=32 tempo=1269ms TTL=42
Resposta de 8.8.8.8: bytes=32 tempo=756ms TTL=42
Resposta de 8.8.8.8: bytes=32 tempo=913ms TTL=42
Resposta de 8.8.8.8: bytes=32 tempo=596ms TTL=42
Resposta de 8.8.8.8: bytes=32 tempo=657ms TTL=42
Resposta de 8.8.8.8: bytes=32 tempo=713ms TTL=42
```

Estatísticas do Ping para 8.8.8.8:

Pacotes: Enviados = 49, Recebidos = 49, Perdidos = 0 (0% de perda),

Aproximar um número redondo de vezes em milissegundos:

Mínimo = 566ms, Máximo = 2256ms, Média = 945ms

Control-C

^C

C:\Users\Asus>arp -a

Interface: 192.168.1.102 --- 0xc

Endereço IP	Endereço físico	Tipo
192.168.1.1	00-25-86-c4-02-46	dinâmico
192.168.1.255	ff-ff-ff-ff-ff-ff	estático
224.0.0.2	01-00-5e-00-00-02	estático
224.0.0.22	01-00-5e-00-00-16	estático
224.0.0.252	01-00-5e-00-00-fc	estático
239.255.255.250	01-00-5e-7f-ff-fa	estático
255.255.255.255	ff-ff-ff-ff-ff-ff	estático

C:\Users\Asus>08-25059840

