

## **TERMO DE ACEITE TÉCNICO**

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Bruno Carvalho de Sá Cliente: VIVO

EmpresaVSAT-IDLink kbpsPlataformaEMC BrasilVIVO-PER-25061860-PB256/128VSAT



# dvb rx show

Satellite (DVB) RX Configuration
----Auto start : Enabled

Max Signalling MODCOD : 23 16APSK-9/10 Max Traffic MODCOD : 28 32APSK-9/10

RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName Name

Enable

\* 0 0 9.320000 12.055825 DVB-S2 102 0 0.0 E

Yes

Satellite (DVB) Receiver Status

Rx State : On

DVB State : Forward link up
Network : 1326, T14R Beam
Frequency : 12.055850 GHz
Symbol Rate : 9.319976 Msps

S2 ModCod

- receiving : 15 8PSK-5/6 - current max : 16 8PSK-8/9

```
Pilot
                   : On
Frame length : Short DVB S2 Mode : ACM
                  : Short
DVB S2 Stream type : MPEG-TS
Roll off
                   : 0.20
SNR
                   : 14.8 dB
Input Power
                   : -37 dBm
# dvb tx show
Satellite (DVB) TX Configuration
______
BUPC status
                  : Enabled
                   : Disabled
IDU Output Power : -20 dBm
IDU Max Output Power: 0.0 dBm
Default CW Frequency: 14.125750 GHz
ATM mode
          : VC-Mux
Header Compression : None
Satellite (DVB) Transmitter Status
: On (DVB-RCS)
IDU Output Power : -19.9 dBm
Es/No : 14 0 37
-----
Header Compression : Disabled
Timing correction : -129 us (262180 us)
Frequency correction: -240 Hz
# ping 8.8.8.8 -if 1 -t
64 bytes from 8.8.8.8: time=680 ms
64 bytes from 8.8.8.8: time=570 ms
64 bytes from 8.8.8.8: time=570 ms
64 bytes from 8.8.8.8: time=560 ms
64 bytes from 8.8.8.8: time=580 ms
64 bytes from 8.8.8.8: time=570 ms
64 bytes from 8.8.8.8: time=580 ms
64 bytes from 8.8.8.8: time=600 ms
64 bytes from 8.8.8.8: time=580 ms
64 bytes from 8.8.8.8: time=580 ms
64 bytes from 8.8.8.8: time=560 ms
64 bytes from 8.8.8.8: time=580 ms
64 bytes from 8.8.8.8: time=570 ms
64 bytes from 8.8.8.8: time=580 ms
64 bytes from 8.8.8.8: time=580 ms
64 bytes from 8.8.8.8: time=560 ms
IP DVB 172.18.132.8 /32
```

