


TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Allan Santos Cliente: VIVO

EmpresaVSAT-IDLink kbpsPlataformaEMC BrasilVIVO-PER-22003991-PI256k/128kVSAT



dvb tx show

Satellite (DVB) TX Configuration

Auto start : Enabled
IDU Output Power : -15 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : 33.7 dBm
EIRP : 47.0 dBW
Default CW Frequency: 0.000000 GHz

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

State : On (TDMA)
IDU Output Power : -19.1 dBm

```
ODU Output Power : 35.9 dBm
EIRP : 47.2 dBW Eb/No : 14.0 dB
Header Compression : Disabled
Timing correction : -252 us (259615 us)
Frequency correction: -220 Hz
# dvb rx show
Satellite (DVB) RX Configuration
______
Auto start : Enabled

Max MODCOD : 23 16APSK-9/10 (SNR threshold: 23.5 dB)

RX watchdog : 15 minute
Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId Enable
* 0 0 9.320000 12.055825 DVB-S2 4 Yes
Satellite (DVB) Receiver Status
_____
           : On
: Forward link up
: 1326, GlobalIPO
Rx State
DVB State
                   : 1326, GlobalIP@Telstar-14R
Network
Frequency : 12.055585 GHz
Symbol Rate : 9.319952 Msps
S2 ModCod
  - receiving : 16 8PSK-8/9
     - current max : 23 16APSK-9/10
              : On
Pilot
Frame length : Short DVB S2 Mode : ACM
DVB S2 Mode
                   : ACM
Roll off
                   : 0.25
SNR : 13.6 dB Input Power : -29 dBm
IP DVB 10.50.0.191/32
Ping desde o MGMT- Server ao IP de trafego e para o DVB.
Ping desde dentro da VSAT 8.8.8.8
# ping 8.8.8.8
64 bytes from 8.8.8.8: time=660 ms
64 bytes from 8.8.8.8: time=640 ms
64 bytes from 8.8.8.8: time=560 ms
64 bytes from 8.8.8.8: time=640 ms
64 bytes from 8.8.8.8: time=630 ms
--- 8.8.8.8 ping statistics ---
5 packets transmitted, 5 received, 0.00 percent packet loss
rtt min/avg/max = 560/620/660 ms
```