

TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Allan Santos Cliente: VIVO

 Empresa
 VSAT-ID
 Link kbps
 Plataforma

 EMC Brasil
 VIVO-PER-25081560-PB
 256/128
 VSAT



dvb tx show

Satellite (DVB) TX Configuration

Auto start : Enabled
IDU Output Power : -22 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : 33.7 dBm
EIRP : 47.0 dBW
Default CW Frequency: 0.000000 GHz

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

State : On (TDMA)

IDU Output Power : -22.7 dBm

ODU Output Power : 33.9 dBm

EIRP : 47.2 dBW

Eb/No : 14.0 dB

Header Compression : Disabled

Timing correction : -200 us (262408 us)

```
Frequency correction: -230 Hz
# dvb rx show
Satellite (DVB) RX Configuration
_____
Auto start : Enabled

Max MODCOD : 23 16APSK-9/10 (SNR threshold: 23.5 dB)

RX watchdog : 15 minute
Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId Enable
* 0 0 9.320000 12.055825 DVB-S2 4 Yes
 1 1
                        0.000000 DVB-S2 2
                                                     No
          0.000000
Satellite (DVB) Receiver Status
_____
           : On : Forward link up
Rx State
DVB State
Network : 1326, GlobalIP@Telstar-14R
Frequency : 12.055539 GHz
Symbol Rate : 9.319878 Msps
S2 ModCod
   - receiving : 16 8PSK-8/9
     - current max : 23 16APSK-9/10
: On
Frame length : Short
DVB S2 Mode : ACM
Roll off
                   : 0.25
SNR : 14.6 dB Input Power : -27 dBm
IP DVB 10.53.0.202/32
Ping desde o MGMT- Server ao IP de trafego e para o DVB.
Ping desde dentro da VSAT 8.8.8.8
# ping 8.8.8.8
64 bytes from 8.8.8.8: time=1900 ms
64 bytes from 8.8.8.8: time=640 ms
64 bytes from 8.8.8.8: time=610 ms
64 bytes from 8.8.8.8: time=700 ms
64 bytes from 8.8.8.8: time=1120 ms
--- 8.8.8.8 ping statistics ---
5 packets transmitted, 5 received, 0.00 percent packet loss
```

rtt min/avg/max = 610/990/1900 ms