

# TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais


NOC/Operador: Wallace Teixeira

Cliente: VIVO

Empresa
EMC Brasil

VSAT-ID VIVO-PER31299341-SP

Link kbps 256k/128k
Plataforma VSAT



## dvb tx show

## Satellite (DVB) TX Configuration

Auto start : Enabled
IDU Output Power : -20 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : 33.2 dBm

EIRP : 46.5 dBW

Default CW Frequency: 0.000000 GHz

ATM mode : VC-Mux Header Compression : None

## Satellite (DVB) Transmitter Status

-----

State : On (DVB-RCS2)
IDU Output Power : -13.1 dBm

ODU Output Power : 33.7 dBm

EIRP : 47.0 dBW Es/No : 10.5 dB

Header Compression: Disabled Timing correction: 30 us (249632 us)

Frequency correction: -170 Hz

# dvb rx show

## Satellite (DVB) RX Configuration

-----

Auto start : Enabled

Max Traffic MODCOD : 23 16APSK-9/10

RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName Name Enable

\* 0 0 30.000000 11.592000 DVB-S2 102 0 0.0 E Yes 1 1 25.333000 11.592000 DVB-S2 4 0 0.0 E Yes

## Satellite (DVB) Receiver Status

-----

Rx State : On

DVB State : Forward link up
Network : 1326, T14R Beam
Frequency : 11.592409 GHz
Symbol Rate : 30.000256 Msps

S2 ModCod

- receiving : 7 QPSK-3/4 - current max : 22 16APSK-8/9

Pilot : On

Frame length : Short DVB S2 Mode : ACM

DVB S2 Stream type: MPEG-TS

Roll off : 0.20 SNR : 15.7 dB Input Power : -23 dBm