


## TERMO DE ACEITE TÉCNICO

Solicitante: PRODEMGE / SEE

NOC/Operadora: Ermínio Júnior Operadora/Cliente: Jean Polini

GRE/Prodemge: João Antinossi Responsável/cliente: Maria Aparecida Silva

> Porta kbps Plataforma Consórcio **VSAT-ID** SEE-DAAS-22021 **VSAT** EMC/Vodanet 2Mbps



## # dvb tx show

## Satellite (DVB) TX Configuration

\_\_\_\_\_

Auto start : Enabled IDU Output Power : -20 dBm IDU Max Output Power: 0.0 dBm ODU Output Power : 33.2 dBm EIRP : 46.5 dBW Default CW Frequency: 0.000000 GHz

: VC-Mux ATM mode Header Compression : UDP/IP

## Satellite (DVB) Transmitter Status

: On (DVB-RCS2)

IDU Output Power : -16.4 dBm

ODU Output Power : 33.2 dBm

EIRP Es/No : 15.0 dB

Header Compression  $\,:\,$  Disabled  $\,$ - HC for RCS2 not supported by HUB

Timing correction : -360 us (281768 us)

Frequency correction: 140 Hz

# dvb rx show

Satellite (DVB) RX Configuration

```
_____
                    : Enabled
Auto start
Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName
                                                                            Name
Enable
* 0 0
         4.883300
                      12.176420 DVB-S2 104
                                                 0
                                                    0.0 E
Yes
 1 1
        16.667000
                      11.962753 DVB-S2 2
                                                 0
                                                    0.0 E
Yes
Satellite (DVB) Receiver Status
_____
Rx State
                  : On
DVB State
                  : Forward link up
                  : 65281, Prodemge@Vodanet
Network
                  : 12.176591 GHz
Frequency
Symbol Rate
                  : 4.882971 Msps
S2 ModCod
     - receiving : 4 QPSK-1/2
- current max : 21 16APSK-5/6
                  : On
Pilot
Frame length
                  : Short
                  : ACM
DVB S2 Stream type : MPEG-TS
Roll off : 0.20
SNR
                  : 14.4 dB
                  : -35 dBm
Input Power
# device show
System Information:
                     : SEE-DAAS-22021
   Name
   Location
                      : DATAS
   Contact
   System Up time : 0 days, 00:22:21 CPU Load : 6%
   System time(UTC) : 05 October 2017 14:52:30
   Broadcast Message : not set
HW:
   Model
                      : SatLink 2000
   HW ID
                      : 120033
   Main board ID
                     : 120026 R6.2
MAC addresses:
   Ethernet (LAN) : 00:20:0e:10:58:34
Satellite (DVB) : 00:20:0e:10:58:34
Disparando 10.148.0.17 com 32 bytes de dados:
Resposta de 10.148.0.17: bytes=32 tempo=577ms TTL=57
Resposta de 10.148.0.17: bytes=32 tempo=591ms TTL=57
Resposta de 10.148.0.17: bytes=32 tempo=594ms TTL=57
Resposta de 10.148.0.17: bytes=32 tempo=552ms TTL=57
Resposta de 10.148.0.17: bytes=32 tempo=567ms TTL=57
Resposta de 10.148.0.17: bytes=32 tempo=585ms TTL=57
Resposta de 10.148.0.17: bytes=32 tempo=538ms TTL=57
Resposta de 10.148.0.17: bytes=32 tempo=572ms TTL=57
Resposta de 10.148.0.17: bytes=32 tempo=564ms TTL=57
Resposta de 10.148.0.17: bytes=32 tempo=597ms TTL=57
Estatísticas do Ping para 10.148.0.17:
   Pacotes: Enviados = 10, Recebidos = 10, Perdidos = 0 (0% de
            perda),
Aproximar um número redondo de vezes em milissegundos:
   Mínimo = 538ms, Máximo = 597ms, Média = 573ms
www.globo.com - ok
```

<u>vww.hotmail.com</u> – ok	
<u>vww.google.com</u> – ok	
<u>www.educacao.mg.gov.br</u> – ok	
esponsável pelo teste de navegação: ome: Maria Aparecida Silva unção: Supervisora lentidade: M4.462214	