



TERMO DE ACEITE TÉCNICO

Solicitante: PRODEMGE / SEE

NOC/Operadora: Gustavo Henrique

Operadora/Cliente: Ederson Martins

GRE/Prodemge: João Antinossi


Responsável/cliente: CARLOS AMÉRICO DE MENEZES JÚNIOR

Consórcio
EMC/Vodanet

VSAT-ID
SEE-OLUA-23824

Porta kbps
2Mbps

Plataforma
VSAT



dvb rx show

Satellite (DVB) RX Configuration

Auto start : Enabled
Max Traffic MODCOD : 23 16APSK-9/10
RX watchdog : 15 minute

| Idx | Pri | SymbRate[Msps] | Freq[GHz] | Mode | PopId | SatId | Pos | SatName | Name |
|--------|-----|----------------|-----------|--------|-------|-------|-------|---------|------|
| Enable | | | | | | | | | |
| * 0 | 0 | 13.333333 | 12.173500 | DVB-S2 | 104 | 0 | 0.0 E | | |
| Yes | | | | | | | | | |
| 1 | 1 | 8.883000 | 12.176420 | DVB-S2 | 2 | 0 | 0.0 E | | |
| Yes | | | | | | | | | |

Satellite (DVB) Receiver Status

Rx State : On
DVB State : Forward link up
Network : 65281, Prodemge@Vodanet
Frequency : 12.173511 GHz
Symbol Rate : 13.333048 Msps
S2 ModCod
- receiving : 4 QPSK-1/2
- current max : 21 16APSK-5/6
Pilot : On
Frame length : Short
DVB S2 Mode : ACM

```
DVB S2 Stream type : MPEG-TS
Roll off           : 0.20
SNR                : 14.7 dB
Input Power        : -41 dBm
#
# dvb tx show
```

Satellite (DVB) TX Configuration

```
-----
Auto start         : Enabled
IDU Output Power   : -18 dBm
IDU Max Output Power: 0.0 dBm
Default CW Frequency: 0.000000 GHz
ATM mode           : VC-Mux
Header Compression : UDP/IP
```

Satellite (DVB) Transmitter Status

```
-----
State              : On (DVB-RCS2)
IDU Output Power   : -18.2 dBm
Es/No              : 16.5 dB
Header Compression : Disabled - HC for RCS2 not supported by HUB
Timing correction  : -434 us (260059 us)
Frequency correction: 70 Hz
```

```
#
# device show
System Information:
  Name           : SEE-OLUA-23824
  Location        : Olhos d agua - MG
  Contact         :
  System Up time  : 0 days, 00:27:33
  CPU Load        : 32%
  System time(UTC) : 01 February 2018 13:29:36
  Broadcast Message : not set
```

```
HW:
  Model           : SatLink 2000
  HW ID           : 120033
  Main board ID   : 120026 R6.2
```

```
MAC addresses:
  Ethernet (LAN)   : 00:20:0e:10:90:4d
  Satellite (DVB)  : 00:20:0e:10:90:4d
```

```
#
# arp show
```

| NetAddr | State | MacAddr | If |
|------------|---------|-------------------|----|
| 10.214.4.2 | Dynamic | 1c:39:47:5b:e2:48 | 1 |

```
C:\Documents and Settings\Administrator>ping 10.214.4.1 -n 10
```

Pinging 10.214.4.1 with 32 bytes of data:

```
Reply from 10.214.4.1: bytes=32 time=544ms TTL=56
Reply from 10.214.4.1: bytes=32 time=561ms TTL=56
Reply from 10.214.4.1: bytes=32 time=545ms TTL=56
Reply from 10.214.4.1: bytes=32 time=530ms TTL=56
Reply from 10.214.4.1: bytes=32 time=543ms TTL=56
Reply from 10.214.4.1: bytes=32 time=561ms TTL=56
Reply from 10.214.4.1: bytes=32 time=520ms TTL=56
Reply from 10.214.4.1: bytes=32 time=539ms TTL=56
Reply from 10.214.4.1: bytes=32 time=565ms TTL=56
```

Reply from 10.214.4.1: bytes=32 time=524ms TTL=56

Ping statistics for 10.214.4.1:

Packets: Sent = 10, Received = 10, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
Minimum = 520ms, Maximum = 565ms, Average = 543ms

Lista de sites acessados:

www.globo.com – ok

www.yahoo.com – ok

www.hotmail.com – ok

www.google.com – ok

www.educacao.mg.gov.br – ok

www.prodemge.gov.br – ok

Responsável pelo teste de navegação:

Nome: CARLOS AMÉRICO DE MENEZES JÚNIOR

Função: Diretor

MASP: 106.3758-5